



Shaws Original 1 1/2 Bowl Fireclay Apron Kitchen Sink

ROHL Kitchen Sinks


RC4019

FEATURES COLORS/FINISHES WARRANTY

- Standard 3 1/2" drain openings
- Acid and alkali resistant glazed surfaces
- Designed to withstand heavy use
- Sink measures 39 1/2" x 18 1/2"
- Due to ±2% dimensions, it is recommended that the cabinet maker <u>wait</u> until your sink is delivered to make the cabinet
- 10" overall depth outside
- 9" internal depth
- Weight 176 lbs.
- Can not be flipped, not finished on all sides
- Due to sink thickness, ISE-type Disposal with Extended Flange #ISE10082 or ROHL 733 Basket Strainer is recommended

- White
- Biscuit

- 1 year on manufacturer defects
- 10 years on fading/staining



There is no recommended method of fitting a Shaws Original Sink. Because of the $\pm 2\%$ dimension possibility of a hand-made product, we recommend that the cabinetmaker wait until the unit that will be installed be on hand before making any cabinetry or counter tops. Hence there is no standard fitting framework or support brackets. The cabinet should be reinforced to hold a 130 lb to 175 lb sink, plus the weight of water. Typically this involved a timber supporting frame with 3/4" plywood deck, or even brick plinth; suitably sized to satisfy the specific requirements. The apron is usually extended 1" to 2" from the front cabinet. We see the sink under mounted under the cabinet top material most of the time, but it can be flush mounted or even raised above the cabinet top. Historically, the fitting of fireclay sinks was dictated by the site and usage requirements, with the plumber/installer making the necessary provision to support the sink.

Consult your local ROHL showroom for additional information and specifications. For complete warranty details and a list of showrooms, go to www.rohlhome.com.