


Water Hammer Arrester

Piston Type Water Hammer Arresters, Series 520-T

Product Description: Recommended for plumbing fixtures in office buildings, retail, schools, hospitals, correctional facilities, and public buildings. Threaded connection piston type water hammer arresters consists of seamless, cold rolled and spun closed copper; pressurized arrester chamber; poly piston with two EPDM O-rings, pressure-lubricated with Dow-Corning 111 Silicone Compound, FDA approved.

Features and Benefits:

- Designed to absorb and control shock pressure in water lines from surges during quick valve closure
- Maximum rated surge pressure: 350 P.S.I.G.
- Operating line flow pressure up to 60 P.S.I.G.
- Working temperature range: 33° to 250° F
- Listed by the American Society of Sanitary Engineers to ASSE 1010 Standard
- Certified and tested by U.S. Testing Co. Inc., Tulsa, OK to ASSE 1010 Standard
- IAPMO Listed, File No. 4785



Threaded Connection Piston Water Hammer Arrester
Series 520-T

WATER HAMMER ARRESTER SIZING CHART

Smith Fig. No.	Pipe Size, NTP	Size	Air Change	Dimensions		Fixture Unit Capacity
				A	B (DIA)	
520-T-AA	1/2"	AA*	60 psig	5.56"	.875"	Residential
520-T-A	1/2"	A	60 psig	6.875"	1.125"	1 to 11
520-T-B	3/4"	B	60 psig	8.69"	1.38"	12 to 32
520-T-C	1"	C	60 psig	12.00"	1.38"	33 to 60
520-T-D	1-1/4"	D	60 psig	12.00"	2.13"	61 to 113
520-T-E	1-1/2"	E	60 psig	14.56"	2.13"	114 to 154
520-T-F	2"	F	60 psig	16.38"	2.13"	155 to 330

For flow pressures up to 60 P.S.I.G.						
Length of Pipe	Nominal Pipe Diameter					
	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
25'	A	A	B	C	D	E
50'	A	B	C	D	E	F
75'	B	C	D	AE	F	EF
100'	C	D	E	F	CF	FF
125'	C	D	F	AF	EF	EFF
150'	D	E	F	DF	FF	FFF

NOTE: Dimensional data is subject to manufacturing tolerances and change without notice

*NOTE: AA size for residential applications only

NOTE: Per ASSE Standard, systems exceeding 60 P.S.I.G. shall be installed with a pressure reducing valve upstream of the unit