

FLAME STOPPER™

3619-5-61
2000
Standard Sealant

- Meets NFPA Class A and complies with ICC IRC 2000
- Noncombustible per ASTM E136
- Seals rigid surfaces where no movement is expected
- Product is a red color

Flame Stopper™ 2000 is a standard inorganic Fire Stop Sealant designed to seal rigid surfaces where no movement occurs. It prevents the spread of toxic fumes, smoke and fire, and dries to a red non-flexible compound. Apply in interior applications only. Dried product can be painted.

Specifications: Tested according to ASTM E136. Meets the criteria for fire, smoke, and draftstop requirements as defined in all major building codes. Consult specific UL system drawings for more detail if needed.

ASTM E84 Rating: Class A
Flame Spread Index: 0
Smoke Developed Index: 0

This product is not UL classified

Use on: All horizontal and vertical joints, “through-penetrations” in drywall, floors, walls and metal pipes. Do not use in areas that experience any movement.

How to apply: Trim nozzle to desired bead size. Puncture seal to permit flow into nozzle. Apply generously to a clean, dust free surface (above 45 °F) with caulk gun in one continuous bead. Tool in place, if needed, before product skins over.

Clean up: Clean up sealant immediately when wet with soap and warm water.

Precautions: Wear suitable protective clothing, chemical resistant gloves and eye protection during application of this product. If the product adheres to exposed skin, sever irritation may occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. For longest life, store in controlled environment, 35 °F - 80 °F. Do not store in direct sunlight. Protect from freezing.

First Aid: For any overexposure or if skin irritation develops, seek immediate medical attention after first aid is given. Should contact be made with eyes, flush for 15 minutes with plenty of clean room temperature water. Should skin contact occur, wash with soap and water. Do not use solvents on the skin. Should ingestion occur, call physician immediately. Do not induce vomiting.

Warranty: All products shown to be defective in manufacture, will be replaced free of charge. Since the use of these products is beyond the manufacturer’s control, we can not assume any risk of liability for results obtained, nor can we accept damages in excess of the purchase price of the product.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
3619-5-61	10 fl.oz.	2" x 2" x 11.5"	10 fl.oz. / 296 mL	1.3 lbs.	12/crtn.	758706361955

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101