









Pollution Control Corp. has been providing Oilfield and Industrial Containment systems since 1992. PCC has a diverse product line of Load Line Containment Systems, ranging from 3 to 29 gallon capacity. The containers are manufactured with UV resistant polyethylene and are available in three colors.



## Load Line Containment - Technical Specifications

Specifications	300	301	305	303
Distance from the ground to the bottom of a 3 inch collar	4.75″	7.5″	7"	17"
Capacity (Gal.)	3	6	9	29
Weight (lbs)	20	25	35	31
Height (in.)	13.5	16.5	19.5	30
Width (in.)	19.25	21.5	26	26
Front to Back (in.)	18.5	21.5	27.5	27.5
Sidewinder	Standard	Standard	Optional	Optional

## **Load Line Containment**

Quality UV resistant polyethylene Eliminates expensive clean up at loading and unloading areas Sidewinder automatically empties unit while truck is loading product Steel collar and saddle gives the 300, 301 and the 302 the strength of steel and the non corrosiveness of polyethelene Ribs have been added to the back of the units to double the strength of the steel saddle Units can be locked for security Valves can be locked inside the 302 and 303 units Stainless steel bolts and hinges Unit is designed to handle oil and saltwater All units come in 2″, 3″ or 4″ collar sizes, with carbon steel standard stainless steel available on request

PCC 303 has a 4-3/4" hole to accommodate all pipe sizes Taller lids available on the 302 and 303 to accommodate gate valves

PCC 302 & 303 units can be locked with valves inside.



PCC 302 & 303 have optional sidewinder installed after the valve.



PCC Load Line Containers are available in yellow, tan or black



Automatically empty your Pollution Control container with the sidewinder, while loading product



PCC Load Line Containers help with compliance of Federal Regulations for spills both inside and outside containment walls.