

## PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 51043

**DESCRIPTION:** 10 AWG SOLID TYPE THHN/THWN INSULATED WIRE

**CONSTRUCTION:** This cable consists of one bare copper conductor with integral insulation and jacket.

APPROVALS: UL Standard 83 and Subject 758

APPLICATION: Insulated Wire, Appliance Wiring Material, Canada T90-Nylon, Canada TWN75

## **Construction Parameters:**

Conductor 10 AWG Bare Copper

Stranding Solid
Insulation Material PVC/Nylon
Insulation Thickness 0.022" Nom.
Nylon Insulation Thickness 0.006" Nom.
Insulated Conductor Diameter 0.158" Nom.
Approximate Cable Weight 37.9 Lbs/1M' Nom.

## **Electrical Properties:**

Temperature Rating -20°C to 105°C

Operating Voltage 600 V RMS Max., 1000V (AWM 1453)

DC Resistance per Conductor @ 20°C 1.00 Ohms/1M' Nom.

Insulation/Jacket Color Varies (Consult factory for availability)

Legend (Surface Ink Print) CCI TRIANGLE 10 AWG (5.26mm²) THHN OR THWN E101736 (UL) 600V OR AWM

STYLE 1317 & 1409 600V & 1453 1000V GASOLINE & OIL RESISTANT I -- C(UL) T90

NYLON OR TWN75 FT1

## This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested. Wire is packaged on standard metal or wooden reels depending on the putup - consult factory.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: February 3, 2011