

Diversey

J-Fill® QuattroSelect® Dispensing System



Wall-mounted dispensing system that accurately dispenses four different products and rinse water in one easy step.

Easy to Use

- Dispenses four products at the push of a button
- Number and color-coded labels for easier product identification
- J-Fill® dispensing system will dispense accurate cleaning solutions with no measuring, mixing or mess
- Fill buckets, autoscrubbers or bottles from a central location accurately and efficiently
- Easy product change-out
- High flow bucket fill and low flow bottle fill

Features

- Air Gap backflow prevention
- One handed low flow bottle filling
- Remote high flow bucket/autoscrubber fill gun
- Smart Valve™ product selection
- Product identification windows
- Drip tray with drain hose
- Rugged powder coated steel construction
- Lockable cabinet with keys
- Design only allows J-Fill® packaging to be used within dispenser
- Uses J-Fill® Spill-Tite™/MC cartridges that are leak proof and virtually eliminates chemical exposure, tampering and manually diluting products
- Metering tip in each J-Fill® cartridge ensures precise dilution and eliminates possibility of tampering with dilution ratios
- J-Fill® dispensers use superconcentrated and hyperconcentrated chemicals, reducing in-use cost, packaging used and solid waste disposal

Designed For

- Healthcare
- Food Service
- Education
- Retail
- BSC
- Government

Use Overview

QuattroSelect® Dispensing System allows you to choose from four different products with the turn of a dial. Simply select the product you desire, choose one handed low flow bottle fill or point of use bucket activation and dispense ready-to-use solutions into spray bottles, buckets and automatic scrubbers. The lockable cabinet helps eliminate unwanted cartridge removal.



Remote high flow bucket activation



High flow and low flow quick change



One handed bottle fill



Product Specifications

Description	
Unit Dimensions	24.25" x 18.5" x 7.5" (62 cm x 47 cm x 19 cm)
Weight	15 lbs./6.8 kg
Weight in Carton	19 lbs./8.6 kg
Carton Dimension	27" x 20.5" x 9.5" (68 cm x 52.1 cm x 24.1 cm)
Low Flow Rate	1.5 gpm (5.1 Lpm)
High Flow Rate	4.0 gpm (15.0 Lpm)
Water In-Let Hose	4' (1.22 m)
Remote Bucket Fill Hose	8' (2.44 m)
Drip Tray Drainage Hose	8' (2.44 m)

Operating Range Requirements

Description	Concentrate
Water Pressure	30–85 psi (170–580 KPA)
Water Flow	> 2.0 gpm
Water Temperature	40–120° F (5–48° C)

ASSE 1055-B backflow prevention requirements.

Available Items

Product Code	Description/Package Size
3764735	J-Fill® QuattroSelect® Air Gap Dispenser / 1 Unit
3754220	J-Fill® QuattroSelect® Safe Gap Dispenser / 1 Unit
5913247	J-Fill® QuattroSelect® Safe Gap dispenser - Solid Door Unit / 1 Unit

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.