Perlator® Faucet Aerator - 2.2 gpm Flow Restricted Junior Size



flow, stop and go®

Features and Benefits

- Watercolours® design: Color coding to identify flow rate and stream pattern.
- Patented construction provides a splash-free stream, well-aerated and soft to the touch.
- Integrated anti-liming honeycomb replaces conventional wire mesh screens prone to lime build up.
- Anti-clogging dome screen filters sediment and particles.
- Available housing finishes: chrome, polished brass, & brushed nickel.
- Roll marked with statutory marks or laser for vandal proof housings.

Certifications

ANSI/NSF $^{\odot}$ -61-372 ASME A112.18.1M and CSA B125 (pending)

Thread & Part Number				
Part #	Designation	Thread Size		
10 965	Insert only			
10 970	Junior male	13/16"-27		
10 980	Junior female	3/4"-27		
10 958	Junior dual thread	13/16"-27 x 3/4"-27		
10 974	Vandal proof junior male	13/16"-27		
10 984	Vandal proof junior female	3/4"-27		
10 959	Vandal proof junior dual thread	13/16"-27 x 3/4"-27		

Other product combinations available.

P	a	c	k	a	α	i	n	α	
•	u	•	• •	u	9	н	•••	9	8

Inserts 1 pc (bag), 6 pcs (tube), 50 pcs (bag)

Jr. male/female 1 pc (bag), 6 pcs (tube), 50 pcs (tray)

Jr. dual thread/vandal proof dual thread


Jr. vandal proof male/female 1 pc (bag), 6 pcs (tlamshell), 50 pcs (tray)

1 pc (bag), 6 pcs (tube), 50 pcs (tray)

Color Code			
Dome	Ring	Basket	
Red	White	Dark Gray	

2.5 2.0 1.5 1.0 0.5 0.0 0.0 10 20 30 40 50 60 70 80 LINE PRESSURE (psi)





Dimensions				
No	mm	In		
Α	18.20	.717		
В	10.20	.402		
С	17.40	.685		
D	≈ 11	≈ 7/16		



VP Junior Male	VP Junior Femal	e VP Jr. Dual Thread			
Technical Data	a				
Materials: Bo	ody	Acetal			
W	asher	EPDM			
Continuou		Short-term (5 minutes max.) Per ASME A112181 testing requirements			
max. 120 (70 <u>max.</u>	max. 160			
°C F 80 ps	5.5bar °C	°F 125psi 8.5bar max.			

NEOPERL®, Inc., Waterbury, CT • Tel: 203-756-8437 • Fax: 203-574-2107 • www.neoperl.com