ROMACINDUSTRIES, INC.

EXTRA DEEP SOCKET

MATERIAL SPECIFICATIONS

Designed for speed, extra deep sockets help to quickly tighten hex nuts on repair clamps, couplings, saddles, tapping sleeves and other fittings.

6-PT Heat treated alloy deep socket for use on long bolts. Silver finish. Socket barrel is carbon steel.

Not for use with power or impact tools.





| SOCKET SIZE | CATALOG NUMBER | OVERALL LENGTH | DRIVE | LIST PRICE | APPROX. WEIGHT (lbs.) |
|-------------|------------------|-------------------|-------|------------|--------------------------|
| 1 1/16" | 1063 DEEP SOCKET | 6 1/4" | 1/2″ | \$84.26 | 1.3 |
| 11⁄4″ | 1250 DEEP SOCKET | 6 1/2" | 1/2" | 93.19 | 1.5 |

OD TAPE MEASURE

MATERIAL SPECIFICATIONS

- Side one features Romac logo side two.
- Side two features pipe O.D. chart.
 You may replace the O.D. chart with your logo for an additional charge.
- Standard inches on top of tape (up to 116").
- Diameter inches to 100ths on bottom of tape (up to 38.30").

| DESCRIPTION | CATALOG NUMBER | APPROX. WEIGHT (lbs.) | LIST PRICE |
|-----------------------------------|-------------------|-----------------------------|---------------|
| Romac Logo Only | 001-0001 | 0.2 # | \$20.95 |
| With Additional Logo ¹ | 001-0002 | 0.2 # | 22.68 |



