

LATERAL TELESCOPING BRACE ASSEMBLY



FEATURES

- Telescoping brace member eliminates the need to cut pipe, minimizing waste and allowing one person to effectively complete the installation
- Easy "push-to-install" nVent CADDY Rod Lock feature allows the V-bolt to assemble quickly
- Electrogalvanized coating throughout the entire assembly provides superior corrosion resistance and a consistent and professional aesthetic
- Designed to reduce the installation time of a complete brace by up to 80%
- · Compact assembly simplifies handling and storage
- Design allows load through the brace member to be distributed through centerline of the service pipe
- Meets requirements of NFPA® 13

Part Number	Length (L)	Pipe Size	Hole Size (HS)	UL Listed Load
CSBT1	12"-18"	1"-4"	1/2"	1,300 lbs
CSBT2	18"-36"	1"-4"	1/2"	1,300 lbs
CSBT3	36"-66"	1"-4"	1/2"	1,300 lbs
CSBT4	66"-84"	1"-4"	1/2"	1,300 lbs

UL Listed Load applies to Sch 40, Sch 10, Youngstown Tube Fire-Flo (1-1/2" to 4") and Bull Moose Eddy Flo (1-1/4" to 4") service pipes.

VERTICAL DISTANCE FROM STRUCTURE TO PIPE CENTERLINE BASED ON 45° BRACE ANGLE

	Nominal Pipe Size				
Part Number	1 in	2 in	3 in	4 in	
CSBT1	10" - 13"	10" - 13"	11" - 14"	11" - 14"	
CSBT2	12" - 22"	12" - 23"	13" - 23"	13" - 24"	
CSBT3	23" - 40"	24" - 41"	24" - 42"	25" - 42"	
CSBT4	41"- 51"	42" - 52"	43" - 52"	43" - 53"	



Our powerful portfolio of brands:

CADDY **HOFFMAN** RAYCHEM **SCHROFF TRACER** ERICO

Improper installation, misuse, misapplication or other failure to completely follow nVent instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.