NuTone

DESCRIPTION

- Efficient ventilation and bright light in one easy installation.
- · Fan and light operate separately or together.
- Quiet operation with one-piece molded blower wheel and silent backdraft damper.
- Attractive grille styling.
- Plug-in motor and light.
- Uses one (1) 100 watt incandescent bulb (bulb not included).
- Refer to NuTone's catalog for a complete listing of accessories to effectively adapt this Ventilation Fan with Light to your construction requirements.

DESIGN FEATURES

| Air Delivery: Sound Level: Dimensions: Lamp: | 50 cfm. 2.5 Sones. Housing: 8¼" x 8" x 5¾". Grille: 12" x 10¾". One 100W maximum A19 (bulb not included) |
|---|--|
| Material & | |
| Component Data: | Housing: Galvanized steel. Grille: White polymeric. Lens: Translucent white polymeric. Reflector: Galvanized steel (white). Damper: Polymeric. |
| Motor: | Plug-in, permanently lubricated. |
| Electrical Rating: | With one (1) 100 watt bulb: 120 VAC, 60 Hz, 1.6 A |
| Blower Wheel: | One-piece polymeric, 4¾" diameter. |
| Duct Size: | 4" diameter. |
| Mounting: | Mounting flange provided. |



Model 763N Ventilation Fan with Light



INSTALLATION

- Suitable for use over tub or shower enclosure when installed in a GFCI protected branch circuit.
- Installation instructions are included with each unit.
- Type IC for use with thermal insulation.
- Not for use with solid state speed controls.
- Not for use in kitchens.

ARCHITECT'S SPECIFICATIONS

Ventilation Fan with Light shall be NuTone Model 763N as manufactured according to listed specifications. Fan shall ventilate 50 cfm at a sound level of 2.5 Sones. Housing shall be $8\frac{1}{4}$ x 8 x $5\frac{3}{4}$ and connect to 4" duct.

| Broan-NuTone LLC | Hartford, Wisconsin | www.nutone.com | 888-336-3948 |
|------------------|---------------------|----------------|--------------|
|------------------|---------------------|----------------|--------------|

| REFERENCE | QTY. | REMARKS | Project |
|-----------|------|---------|-------------------|
| | | | Location |
| | | | Architect |
| | | | Engineer |
| | | | Contractor |
| | | | Submitted by Date |

PERFORMANCE RATINGS MODEL 763N FAN / LIGHT

HVI PERFORMANCE

| Model | Static Pressure (Ps) | CFM | Sones | Fan Watts |
|-------|-------------------------|-----|-------|--------------|
| 763N | 0.10 | 50 | 2.5 | 42.4 |
| | 0.25 | 39 | | 41.6 |



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

AMPS -

| Model | Amps |
|-------|------|
| 763N | 1.6 |

| Model | Weight | |
|-------|----------|--|
| 763N | 6.0 lbs. | |







NuTone

AIR FLOW PERFORMANCE MODEL 763N



Broan-NuTone LLC Hartford, Wisconsin www.nutone.com 888-336-3948