



L & M 70 Gram Silt Fence Fabric Specifications

To whom it may concern:

Subject: **Certification L & M 70 Gram Silt Fence Fabric**

This letter certifies that our **L & M 70 Gram Silt Fence Fabric** meets and/or exceeds the specifications listed below. Our 70 gram silt fence fabric meets the FDOT Section 199 requirements for Staked Silt Fence. The average laboratory test values for the **L & M 70 Gram Silt Fence Fabric** are as follows:

Property	Test Procedure	American Standard
Grab Tensile	ASTM D 4632	114
Grab Elongation	ASTM D 4632	27%
Trapezoid Tear	ASTM D 4533	55 lbs
Apparent Opening Size	ASTM D 4751	40 sieve
Flow Rate	ASTM D 4491	25 gpm/ft
Permittivity	ASTM D 4491	0.1sec
UV Resistance	ASTM D 4355	80% @ 500 hrs
Roll Width		2 or 3 ft

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quentin McMillan