Kidde Engineered Fire Suppression System

Designed for use with 3M™ Novec™ 1230 Fire Protection Fluid



Effective: March 2007

K-45-4080

Corner Pulleys Data Sheet

FEATURES

• For Use with UL, ULC and FM Approved Systems

P/N: 803808 AND 844648

P/N: 80380 WATERTIGHT **CORNER PULLEY** 1.75 in. GASKET (45 mm) COVER-BODY 2.13 in. (54 mm) DIA. COVER SCREW 0.62 in. 3/8-18 NPS (16 mm) (FEMALE) 0.81 in.

MATERIAL COVER AND BODY: BRASS GASKET: RUBBER

P/N: 844648
1/2" E.M.T.
CORNER PULLEY

COVER SCREW

(2) 1/2" E.M.T.
CONNECTIONS
COMPRESSION TYPE

2.75 in.
(70 mm)
APPROX.

MATERIAL COVER AND BODY: BRASS GASKET: RUBBER

Kidde is a registered trademark of Kidde-Fenwal, Inc. 3M and Novec are trademarks of 3M. All other trademarks are property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly.

If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721. Telephone: (508) 881-2000.

Kidde Fire Systems A UTC Fire & Security Company 400 Main Street Ashland, MA 01721 Ph: 508.881.2000 Fax: 508.881.8920

www.kiddefiresystems.com