

DA68-02897A-06.indb 01 2014. 5. 13. 11:50

safety information

SAFETY INFORMATION

Before using your new Samsung French Door Refrigerator, please read this manual thoroughly to ensure that you know how to operate the features and functions that your new appliance offers safely and efficiently. This appliance is not intended for use by persons (including children) with reduced physical, sensory, or mental capabilities, or those who lack experience and knowledge, unless they have been given supervision or instruction concerning the use of the appliance by a person responsible for their safety. Because the following instructions cover various models, the characteristics of your refrigerator may differ slightly from the refrigerator described in this manual. If you have any question, contact us at 1-800-SAMSUNG or find help and information online at www.samsung.com.

Important safety symbols and precautions:

△ WARNING

Hazards or unsafe practices that may result in severe personal injury or death.

Hazards or unsafe practices that may result in minor personal injury or property damage.

0	Do NOT attempt.
\otimes	Do NOT disassemble.
8	Do NOT touch.
*	Follow directions carefully.
3	Unplug the power plug from the wall socket.
	Make sure the refrigerator is grounded to prevent electric shock.
	Call the contact center for help.
B	Note.

These warning symbols are here to prevent injury to you and others. Please follow them carefully. After reading this section, keep it in a safe place for future reference.

△ WARNING

CRITICAL INSTALLATION WARNINGS



- location or place where it may come in contact with water.
- Deteriorated insulation on electrical parts may cause an electric shock or fire.
- . Do not place this refrigerator in direct sunlight or expose it to the heat from stoves, room heaters, or other appliances.
- . Do not plug several appliances into the same multiple power strip. The refrigerator should always be plugged into its own individual electrical outlet which has a voltage rating that matches the voltage listed on the refrigerator's rating plate.
- This provides the best performance and also prevents overloading house wiring circuits, which could cause a fire hazard from overheated wires.
- . If the wall socket is loose, do not insert the
- There is a risk of electric shock of fire.
- . Do not use a cord that shows cracks or abrasion damage along its length or at either
- . Do not bend the power cord excessively or place heavy articles on it.
- · Do not twist or tie the power cord.
- . Do not hook the power cord over a metal object, place a heavy object on the power cord, insert the power cord between objects, or push the power cord into the space behind the appliance.
- When moving the refrigerator, be careful not to roll over or damage the power cord
- This may result in an electric shock or fire.
- · Never unplug your refrigerator by pulling on the power cord. Always grip the plug firmly and pull straight out from the outlet.
- Damage to the cord may cause a short-circuit,

02 Safety information

DA68-02897A-06.indb 02 2014. 5. 13. 11:50

- fire, and or electric shock.
- · Do not use aerosols near the refrigerator.
- Using aerosols near the refrigerator may cause an explosion or fire.
- Do not install this appliance near a heater or inflammable material.
- Do not install this appliance in a humid, oily or dusty location, in a location exposed to direct sunlight and water (rain drops).
- Do not install this appliance in a location where gas may leak.
- This may result in an electric shock or fire.



- This refrigerator must be properly located and installed in accordance with the instructions in this manual before you use it.
- Connect the power plug in the proper position with the cord hanging down.
- If you connect the power plug upside down, the wire can get cut off and cause a fire or electric shock.
- When moving the refrigerator, be careful not to roll over or damage the power cord.
- This constitutes a fire hazard.
- Make sure that the power plug is not squashed or damaged by the back of the retrigerator.
- Keep the packing materials out of reach of children.
- There is a risk of death from suffocation if a child puts the packing materials on his or her head.
- The appliance must be positioned so that the plug is accessible after installation.
- Failing to do so may result in an electric shock or fire due to electric leakage.
- You need to remove all the protective plastic film before you initially plug the product in.



- The refrigerator must be safely grounded.
- Always make sure that you have grounded the refrigerator before attempting to investigate or repair any part of the appliance. Power leakages can cause severe electric shock.
- Never use gas pipes, telephone lines, or other potential lightning attractors as an electrical ground.
- Improper use of the grounding plug can result in a risk of electric shock. If it is necessary to use an extension cord, use only a 3-wire extension cord that has a 3-blade grounding plug and a 3-slot receptacte that will accept the plug on the appliance. The marked rating

- of the extension cord should be AC115-120 V, 10 A, or more. If a grounding adapter is used, make sure the receptacle box is fully grounded.
- Plug the power plug into the wall socket firmly.
 Do not use a damaged power plug, damaged power cord or loose wall socket.
- This may result in an electric shock or fire.



 If the power cord is damaged, have it replaced immediately by the manufacturer or one of its service agent.

A CAUTION

INSTALLATION CAUTIONS



- Allow sufficient space around the refrigerator and install it on a flat surface.
- If your refrigerator is not level, the internal cooling system may not work correctly.
- Keep the ventilation space in the appliance enclosure or mounting structure clear of obstructions.
- Allow the appliance to stand for 2 hours after installation.
- We strongly recommend you use a qualified technician or service company to install the refrigerator.
- Failing to do so may result in an electric shock, fire, explosion, problems with the product, or injury.

A WARNING

CRITICAL USAGE WARNINGS



- Do not insert the power plug into a wall socket with wet hands.
- Do not store articles on the top of the appliance.
- When you open or close the door, the articles may fall and cause personal injury and/or material damage.
- Do not insert hands, feet or metal objects (such as knives, etc.) into the bottom or the back of the refrigerator.
- This may result in an electric shock or injury.
- Any sharp edges may cause a personal injury
- Do not put a container filled with water on the refrigerator.
- If spilled, there is a risk of fire or electric shock.
- Children should be supervised to ensure that Safety information _03

DA68-02897A-06.indb 03 2014.5.13. 11:50

- they do not play with the appliance.
- Keep fingers out of "pinch point" areas.
 Clearances between the doors and cabinet are necessarily small. Be careful when you open the doors when children are in the area.
- Do not let children hang on the door. A serious injury may occur.
- Do not let children go inside the refrigerator.
 Children could become trapped.
- Do not insert your hands into the bottom area under the appliance.
- Any sharp edges may cause personal injury.
- . Do not let children step on a drawer cover.
- The drawer may break and cause them to slip.
- . Do not overfill the refrigerator with food.
- When you open the door, an item may fall out and cause personal injury or material damage.
- Do not touch the inside walls of the freezer or products stored in the freezer with wet hands.
- This may cause frostbite.
- Never put fingers or other objects into the water dispenser hole, ice chute, or ice maker bucket.
- It may cause personal injury or material damage.
- Do not use or place any substances sensitive to temperature such as inflammable sprays, inflammable objects, dry ice, medicine, or chemicals near or inside of the refrigerator.
- Do not keep volatile or inflammable objects or substances (benzene, thinner, propane gas, alcohol, ether, LP gas and other such products etc.) in the refrigerator.
- This refrigerator is for storing food only.
- This may result in fire or explosion.
- Do not store pharmaceutical products, scientific materials, or temperature sensitive products in the refrigerator.
- Products that require strict temperature controls must not be stored in the refrigerator.
- Do not place or use an electrical appliance inside the refrigerator, unless it is of a type recommended by the manufacturer.
- Do not stand on top of the appliance or place objects (such as laundry, lighted candles, lighted cigarettes, dishes, chemicals, metal objects, etc.) on the appliance. This may result in an electric shock, fire, problems with the product, or injury. Do not put a container filled with water on the appliance.
- If spilled, there is a risk of fire or electric shock.
- . Do not use mechanical devices or any other

- means to accelerate the defrosting process, other than those recommended by the manufacturer.
- · Do not damage the refrigerant circuit.
- Do not spray volatile material such as insecticide onto the surface of the appliance.
- As well as being harmful to humans, it may also result in an electric shock, fire or problems with the product.
- Never stare directly at the UV LED lamp for long periods of time.
- This may result in eye strain due to the ultraviolet rays.



- Do not attempt to repair, disassemble, or modify the appliance yourself.
- Do not use any fuse (such as cooper, steel wire, etc.) other than the standard fuse.
- If your appliance needs to be repaired or reinstalled, contact your nearest service center.
- Failing to do so may result in an electric shock, fire, problems with the product, or injury.
- If the interior or exterior LED lamp has gone out, please contact your nearest service center.



- Children should be supervised to ensure that they do not play with the appliance.
- Keep fingers out of "pinch point" areas: clearances between the doors and cabinet are necessarily small. Be careful when you open the doors when children are in the area. Do not let children hang on the door. If not, a serious injury may occur. Risk of children entrapment. Do not let children enter inside the refrigerator.
- Bottles should be stored tightly together so that they do not fall out.
- This product is intended only for the storage of food in a domestic environment.
- If a gas leak is detected, avoid any naked flames or potential sources of ignition and air the room in which the appliance is standing for several minutes.
- Do not touch the appliance or power cord.
- Do not use a ventilating fan.
- A spark may result in explosion or fire.
- Use only the LED Lamps provided by the manufacturer or its service agents.



 If the refrigerator emits a burning smell or smoke, unplug the refrigerator

04_ Safety information

DA68-02897A-06.indb 04 2014. 5. 13. 11:50

- immediately and contact your Samsung Electronics service center.
- If you experience difficulty changing a non-LED light, contact a Samsung service energy.
- If the product is equipped with LED Lamps, do not disassemble the Lamp Covers and LED Lamps yourself.
- Please contact your service agents.
- If dust or water enters the refrigerator, unplug the refrigerator and contact your Samsung Electronics service center.
- Otherwise there is a risk of fire.

A CAUTION

USAGE CAUTIONS



- Do not re-freeze frozen foods that have thawed completely. Do not place carbonated or fizzy drinks in the freezer compartment. Do not put bottles or glass containers in the freezer.
- When the contents freeze, the glass may break and cause personal injury.
- Use only the ice maker provided with the refrigerator.
- Have the refrigerator's water supply installed by a suitably qualified person and connected only to a potable water supply. To operate the ice maker properly, water pressure of 20 – 125psi (138 – 862 kPa) is required. If you will be away from home for a long period of time (on vacation, for example) and won't be using the water or ice dispensers, close the water valve.
- Otherwise, water leakage may occur.
- If you won't be using the refrigerator for a very long period of time, (3 weeks or more) empty the refrigerator, unplug it, close the water valve, wipe excess moisture from the inside walls, and leave the doors open to prevent odors and mold.



- Service Warranty and Modification.
 Any changes or modifications performed by a 3rd party on this finished appliance are not covered under Samsung warranty service, nor is Samsung responsible for safety issues that result from 3rd party modifications.
- Do not block the air vents inside the refrigerator.
- If the air vents are blocked, especially with

- a plastic bag, the refrigerator can be over cooled. If this cooling period lasts too long, the water filter may break and cause water leakage.
- If the refrigerator is disconnected from the power supply, you should wait for at least five minutes before plugging it back in.
- If you have a long vacation planned or do not intend to use the refrigerator for a long period of time, (3 weeks or more) empty the refrigerator, pull out the power plug, close the water valve, wipe excess moisture from the inside walls, and leave the doors open to prevent odors and mold.
- Letting the refrigerator run long periods of time without using it can cause the insulation to deteriorate and may cause a fire.
- . To get the best performance from the product:
- Do not place food too close to the vents at the rear of the appliance as it can obstruct free air circulation in the refrigerator compartment.
- Wrap food up properly or place it in airtight containers before putting it into the refrigerator.
- Do not place glass or bottles or carbonated beverages into the freezer.
 The container may freeze and break, and this may result in injury.
- Please observe maximum storage times and expiration dates of frozen goods.
- There is no need to disconnect the refrigerator from the power supply if you will be away for less than three weeks. However, if you will be away for more than three weeks, remove all the food, unplug the refrigerator, close the water valve, wipe excess moisture from the Inside walls, and leave the doors open to prevent odors and mold.
- Fill the water tank, ice tray and water cubes only with potable water (mineral water or purified water).
- Do not fill the tank with tea or a Sports drink.
 This may damage the refrigerator.
- Do not apply strong shock or excessive force onto the surface of glass.
- Broken glass may result in a personal injury and/or property damage.



- If the product is flooded, make sure to contact your nearest service center.
- There is a risk of electric shock or fire.

Safety information _05

DA68-02897A-06.indb 05 2014, 5, 13. 11:50

A CAUTION

CLEANING CAUTIONS



- Do not directly spray water on the inside or outside the refrigerator.
- There is a risk of fire or electric shock.
- Do not use a hair dryer to dry the inside of the refrigerator. Do not place a lighted candle in the refrigerator to remove bad odors.
- This may result in an electric shock or fire.



- Remove any foreign matter or dust from the power plug pins. Do not use a wet or damp cloth when cleaning the plug.
- Otherwise, there is a risk of fire or electric shock.



- Before cleaning or performing maintenance, unplug the appliance from the wall socket.
- Failing to do so may result in an electric shock or fire.

WARNING

 This product contains chemicals known to the State of California to cause cancer and reproductive toxicity.

MWARNING

CRITICAL DISPOSAL WARNINGS



- DANGER: Risk of child entrapment.
 Before you throw away your old refrigerator or freezer:
- Take off the doors and door latch.
- Leave the shelves in place so that children cannot easily climb inside.
- Children trapped inside a refrigerator can hurt themselves or suffocate to death.
- Please dispose of the packaging material from this product in an environmentally friendly manner.

06_ Safety information

- Ensure that none of the pipes on the back of the appliance are damaged prior to disposal.
- R-600a or R-134a is used as a refrigerant.
 Check the compressor label on the rear of
 the appliance or the rating label inside the
 fridge to see which refrigerant is used for your
 refrigerator. If this product contains flammable
 gas (Refrigerant R-600a), contact your local
 authority in regard to safe disposal of this
 product.
- When disposing of this refrigerator, remove the door/door seals and door latch so that small children or animals cannot become trapped inside. Children should be supervised to ensure that they do not play with the appliance.
 If trapped inside, the child may not hurt or
- If trapped inside, the child may get hurt or suffocate to death.
- Cyclopentane is used in the insulation. The gases in the insulation material require a special disposal procedure. Please contact your local authorities in regard to the environmentally safe disposal of this product.
- Keep all packaging materials well out of the reach of children, as packaging materials can be dangerous to children.
- If a child places a bag over his or her head, the child could suffocate.

ADDITIONAL TIPS FOR PROPER USAGE

- In the event of a power failure, call the local office of your Electricity Company and ask how long it is going to last.
- Most power failures that are corrected in an hour or two will not affect your refrigerator temperatures. However, you should minimize the number of door openings while the power is off.
- But Should the power failure last more than 24 hours, remove and discard all frozen food.
- If a key is provided with refrigerator, the keys should be kept out of the reach of children and not be in the vicinity of the appliance.

DAS8-02897A-06.indb 06 2014, 5, 13. 11:50

- The appliance might not operate consistently (frozen contents can thaw or temperatures can become too warm in the frozen food compartment) when sited for an extended period of time in a location where ambient air temperatures are constantly below the temperatures for which the appliance is designed.
- Do not store food which goes bad easily at low temperature, such as bananas and melons.
- Your appliance is frost free, which means there is no need to manually defrost your appliance. This will be carried out automatically.
- Temperature rise during defrosting complies with ISO requirements. But If you want to prevent an undue rise in the temperature of the frozen food while the appliance defrosts, wrap the frozen food in several layers of newspaper.
- Any increase in the temperature of frozen food during defrosting can shorten its storage life.
- Do not re-freeze frozen foods that have thawed completely.

Saving Energy Tips

- Install the appliance in a cool, dry room with adequate ventilation. Ensure that it is not exposed to direct sunlight and never put it near a direct source of heat (radiator, for example).
- Never block any vents or grilles on the appliance.
- Allow warm food to cool down before placing it in the appliance.
- Put frozen food in the refrigerator to thaw.
 You can then use the low temperatures of the frozen products to cool food in the refrigerator.
- Do not keep the door of the appliance open for too long when putting food in or taking food out. The shorter the time the door is open, the less frost build-up you'll have in the freezer.
- Provide sufficient clearance to the right, left, back, and top when installing for air circulation.
 This will help reduce power consumption and keep your energy bills lower.

Safety information _07

DA68-02897A-06.indb 07 2014, 5, 13. 11:50

contents

SETTING UP YOUR FRENCH DOOR REFRIGERATOR	 09
OPERATING YOUR FRENCH DOOR REFRIGERATOR	 16
TROUBLESHOOTING	2

08_ Safety information

DA68-02897A-06.indb 08 2014. 5. 13. 11:50

Setting up your French Door Refrigerator

GETTING READY TO INSTALL THE REFRIGERATOR

Congratulations on your purchase of this Samsung French Door Refrigerator.

We hope you enjoy the state-of-art features and efficiencies that this new appliance offers.

Selecting the best location for the refrigerator

Choose:

- · A location with easy access to a water supply.
- · A location without direct exposure to sunlight.
- · A location with a level floor.
- A location with enough space for the refrigerator doors to open easily.
- A location that allows sufficient space to the right, left, back and top for air circulation.
- A location that allows you to move the refrigerator easily if it needs maintenance or service.
- Do not install the refrigerator where the temperature will go below 50 °F (10 °C).
- Do not locate the refrigerator where it may become wet.


If the refrigerator does not have enough space, the internal cooling system may not work properly. If your refrigerator has an ice maker, allow extra space at the back for the water line connections. When you install the refrigerator next to a fixed wall, you need a minimum clearance of 3 ¾* (95 mm) between the refrigerator and wall to allow the door to swing open.


Important: Make sure that you can easily move your refrigerator to its final location by measuring doorways (both width and height), thresholds, ceilings, stairways, etc.

The following chart details the exact height and depth of this Samsung French Door Refrigerator.



Model	RF24FS**
Depth "A"	28 5/8" (726 mm)
Width "B"	35 6/8" (908 mm)
Height "C"	68 7/8* (1749 mm)
Overall Height "D"	70° (1777 mm)
Depth "E"	31" (788 mm)







Each measurement based on the design dimension, so it may differ depending on the measuring method.

setting up _09

DA68-02897A-06.indb 09 2014.5.13. 11:50

When moving your refrigerator

To prevent floor damage, be sure the front adjusting legs are in the up position (above the floor). Refer to 'Adjusting the Level' in the manual (on page 13).



Flat-blade screw Control Lever driver(-)

FLOORING


For proper installation, you must place this refrigerator on a level, hard surface that is the same height as the rest of the floor. This surface should be strong enough to support a fully loaded refrigerator.

To protect the finish of the flooring, cut a large section of the cardboard carton and place it under the refrigerator where you are working. When moving the refrigerator, you need to pull and push it straight forwards or back. Do not wiggle it from side to side.



ACCESSORIES AND REQUIRED TOOLS

The following accessories are included with your refrigerator:



10_ setting up


Required Tools (Not provided)

You need the following tools to complete the installation of your refrigerator:

(ED)		-
Philips screwdriver(+)	Flat-blade screw driver(-)	Socket wrench (10mm)
Pliers	Allen wrench (3/16") (5mm)	

REMOVING THE REFRIGERATOR DOORS

For some installations you need to remove the fridge and freezer drawers so you can move the refrigerator to its final location. Do not remove the doors/drawer if you don't need to. If you do not need to remove the refrigerator doors, go to Adjusting the Level on page 13, if you need to remove the doors, continue below. Before removing the door/drawer, make sure you read the following items:






- Be careful not to drop, damage, or scratch the doors/drawers while removing them.
- Use care when you remove the doors/drawers.
 The doors are heavy and you could injure yourself.
- · Reattach the doors/drawers properly to avoid:
- Moisture from air leakage.
- Uneven door alignment.
- Wasting energy due to improper door seal.

Disassemble the refrigerator doors

Be careful not to drop and scratch the watering doors while removing them.


DA68-02897A-06.indb 10 2014. 5. 13. 11:50

1. Remove the 3 screws holding down the TOP TABLE (1) and separate the connected wires.




2. Disconnect the two connectors (2) on the left side door. To remove the water coupler from the hinge, twist and pull it from the hinge. Remove the water line (3) while pressing the marked part (4) of the water line coupler.

If a red clip is on the coupler, you must If a red clip is on the coupler, you mu
caution remove it before removing the tube:




3. Pull and remove the hinge lever (5). Remove the ground screw (6) attached to the upper left door hinges with a philips screwdriver (+). Remove the upper left and right door hinges



- 4. Open the door (more than 90°), lift from the middle hinge and remove the door.
- Due to its design features, you can disassemble and re-assemble the door when the door is open. (The holes in the Door Shaft and the Door Middle Hinge are deliberately tilted at specific angles so that it is difficult to disassemble and re-assemble with the door closed.)



Place the door, inside facing up, on a non-Place the door, insk caution scratching surface.




- If the Auto Closing Hinge is aligned to be vertical as shown in the figure, align it to be parallel by using the Door Middle Hinge. (Refer to No.5 for the disassembly of the Door Middle Hinge)

Do not use a flat head screwdriver to align Do not use a flat head screwdriver to align caution the Auto close Hinge. It may get damaged. Use the Door middle Hinge instead.



5. Remove the screw (8) attached to the lower left and right door hinges with a philips screwdriver (+). Remove the 2 hex head bolts (9) attached to the lower left and right door hinges with an allen wrench (3/16"). Remove the lower left and right door hinges (10)



setting up _11

DA68-02897A-06.indb 11 2014. 5. 13. 11:50






RE-ATTACHING THE REFRIGERATOR DOORS

To reattach the fridge doors after you have moved the fridge to its final location, assemble the parts in reverse order.


1. The Water Line must be fully inserted into the center of the transparent coupler (Type A) or the Guide Lines (Type B) to prevent water leakage from the dispenser.




2. Insert the clip in the install pack and check that it holds the line firmly.

DISASSEMBLING THE FLEX DOOR

1. Take out the Flex Zone (1) by lifting it up.




2. Take off the cover (2) w/harness with a flatblade screwdriver (-).



3. Press the locking tab and separate the Wire Connector.

12_setting up



When reassembling it, be sure to connect causes the wire harness.

If it is not connected, the Flex Room does not work.

4. Remove 1 hex head bolt from each side with a socket wrench (10mm).



5. Lift up the Flex door from the rails.



Putting too much food into the freezer from Putting too much food into the freezer closing completely and can cause frost build-up.





DA68-02897A-06.indb 12 2014. 5. 13. 11:50

RE-ASSEMBLING THE FLEX DOOR

To reattach the flex doors, assemble parts in reverse order.

Be sure to connect the Flex Door Wire Connector.

If it is not connected, the Flex Room does not work.

DISASSEMBLING THE FREEZER DOOR


1. Take out the upper drawer by lifting it up



2. Remove the freeze room guard (1) by lifting the guard up.



3. Take out the lower basket (2) by lifting the basket up from the rail system.



4. Press the fixing hook of the rail system,



5. Holding the top of the Freezer Drawer, pull it out all the way, and then remove it from the rail system.



Be careful not to scratch or dent the caution sliding rail by letting it strike the floor. Be careful not to scratch or dent the

Make sure that you mount the freezer caution basket in the right position when removing / installing the freezer door. Failing to do so may result in the door not opening or closing properly.

Putting too much food into the freezer Putting too much tood into the ineezer from drawers can prevent the freezer from closing completely and can cause frost build-up.









RE-ASSEMBLING THE FREEZER DOOR

To reattach the drawer after you have moved the fridge to its final location, assemble the parts in reverse order.

ADJUSTING THE LEVEL

Make sure the refrigerator is level so that you can make final adjustments. Use a level to test if the refrigerator is level both side to side and back to front. If the refrigerator is not level, you will not be able to get the doors perfectly even, which may cause moisture condensation and increased energy bills. Below is an example of how to level the refrigerator if the left side of the refrigerator is lower than the right side.

How to adjust the level

- 1. Open the freezer drawer and remove the lower
- 2. Insert a flat-blade screwdriver (-) into the notch on the left control lever, and turn it counterclockwise to level the refrigerator. (You turn the lever clockwise to lower the refrigerator and counterclockwise to raise it.)


setting up _13


DA68-02897A-06.indb 13 2014. 5. 13. 11:50






flat-blade screwdriver (-) Control Lever









MAKING MINOR ADJUSTMENTS TO THE DOORS


Remember, a leveled refrigerator is necessary for getting the doors perfectly even. If you need help, review the previous section on leveling the refrigerator.



The left door is fixed. To make minor door adjustments, adjust only the right door.

- Pull out the flex door (1) to reveal the lower hinge (2).
- Insert the supplied allen wrench (5/32*) (3) into the shaft (4) of the lower hinge.
- Adjust the height by turning the hex wrench (3) clockwise (com) or counter clockwise (com).





INSTALLING THE WATER DISPENSER LINE

A water dispenser with a filter is one of the helpful features on your new refrigerator. To help promote better health, the water filter removes unwanted particles from your water. However, it does not sterilize or destroy microorganisms. You may need to purchase a water purifying system to do that. The water line also connects to the ice maker. For the ice maker to operate properly, water pressure of 20-125 psi (138 – 862 kPa) is required.

If the refrigerator is installed in an area with low water pressure (below 20 psi), you can install a booster pump to compensate for the low pressure.

After you have connected the water line, make sure the water storage tank inside the refrigerator is properly filled. To do this, press the water dispenser lever until the water runs from the water water.



Water line installation kits are available at extra cost from your dealer.


We recommend using a water line installation kit that contains copper tubing and ¼" compression nut.

Connecting to the water supply line

 First, shut off the main water supply.




Locate the nearest cold water drinking line and install the pipe clamp and shut off valve.



14_ setting up

DA68-02897A-06.indb 14 2014. 5. 13. 11:50

Connect the water line installation kit to the shut off valve.




Connecting the water supply line to the refrigerator.

There are several items that you need to purchase to complete this connection.

You may find these items sold as a kit at your local hardware store.

Use Copper Tubing	Use Plastic Tubing	
%" copper tubing %" compression nut (1pc) Ferrule (2pc)	%" plastic tobing Molded end(Bulb) %" compression nut (1pc)	



- Connect the household water line to the assembled compression fitting.
- If you are using copper tubing, slip the compression nut (B) (not supplied) and ferrule (not supplied) on the copper tubing (not supplied) as shown.
- If you are using plastic tubing (B), insert the molded end (Bulb) of the plastic tubing (B) into the compression fitting.

Do not use without the molded end (Bulb)

of the plastic tubing (B).

- Tighten the compression nut (B) onto the compression fitting.
- Do not over-tighten the compression nut (B).

 3. Turn the water on and check for any leakage. If you find water drops or leakage in the connection areas, turn off the main water supply. Check the connections and, if necessary, tighten.
- 4. Flush 1 gallon of water through the filter before drinking or using the water from the refrigerator. (Flush approximately 6 minutes.) To flush, press a large glass or cup against the water dispenser lever. Fill the glass, empty it into the kitchen sink after it is filled, and then repeat.
- After you turn on the refrigerator, let the ice maker make ice for 1 to 2 days. Over that period of time, throw out the first 1 or 2 buckets of ice the freezer makes to ensure all impurities have been removed from the water line.

Only connect the water line to a drinkable water source.

If you have to repair or disassemble the water line, cut off 1/4" of the plastic tubing to make sure you get a snug, leak-free connection.



You can test the water line quickly using a paper cup. Under normal conditions, the water dispenser can fill a 5.75 oz. (170cc) cup in about 10 seconds.

COMPLETING THE SET UP

Now that you have your new refrigerator installed in place, you are ready to set up and enjoy the features and functions of the appliance. By completing the following steps, your refrigerator should be fully operational.

- Make sure your refrigerator is in an appropriate location with reasonable clearance between it and the wall. Refer to installation instructions in this manual.
- Once the refrigerator is plugged in, make sure the interior light comes on when you open the doors.
- Set the Temperature control to the coldest temperature and wait for an hour. The freezer will get sightly chilled and the motor will run smoothly. Reset the refrigerator and freezer to the temperatures you want.
- After you plug the refrigerator in, it will take a few hours to reach the appropriate temperature. You can store food and drinks in the refrigerator after the temperature is sufficiently cool.

If condensation or water drops appears on both sides of fridge door's central part, turn the Energy Saver mode off after removing the condensation. (See the explanation on Energy Saver button in the USING THE CONTROL PANEL).

setting up _15

DA68-02897A-06.indb 15 2014. 5. 13. 11:50

SETTING HP

Operating your French Door Refrigerator

USING THE CONTROL PANEL

RF24FS**



(1) Energy Saver Touching this button turns Energy Saver mode on and off. When you turn Energy Saver on, the Energy Saver icon lights. Turn Energy Saver off and the icon goes off. The Energy Saver function's factory setting is "ON". If condensation or water drops appear on the doors, turn the Energy Saver mode off.



(2) Freezer (Hold 3 sec for Power Freezer)

The Freezer button serves two purposes:

To set the Freezer to your desired temperature.

To turn the power freezer function on and off,

1) To set the Freezer temperature
Touch the Freezer button to set the
Freezer to your desired temperature. You
can set the temperature between 5 °F
(-15 °C) and -8 °F (-23 °C).

 Power Freezer function
 Touch and hold this button for 3 seconds to decrease the time needed to freeze products in the Freezer.



It can be helpful if you need to quickly freeze easily spoiled items or if the temperature in the freezer has warmed dramatically (For example, if the door was left open).

When you use this function the energy consumption of the refrigerator will increase. Remember to turn it off when you don't need it and return the freezer to your original temperature setting. If you need to freeze large amount of food stuff, activate Power Freeze function at least 24 hours before.

Alram (Hold 3 sec for Filter The Alarm button serves two purposes:

To turn the door open alarm on and off To reset the water filter life indicator.

I) Door Alarm Function
If the door alarm is set to On, an alarm
beeps if any refrigerator door is left open
for more than three minutes. The beeping
stops when you close the door. The door
alarm function is pre-set to On in the
factory. You can turn it off by pressing and
then releasing the Alarm button. You can
turn it back on in the same fashion. The
icon lights up when the function is on.
When the Door Alarm function is on and
the alarm sound is triggered, the Door
Alarm icon will blink while the alarm



2) Water Filter Life Indicator Function After you replace the water filter, touch and hold this button for 3 seconds to reset the water filter life indicator. When you reset the water filter life indicator, the Filter icon on the panel turns Off. The Filter icon will turn red to let you know it is time to change the water filter after six months (about 300 gallons). Some areas have large amounts of lime in their water, which causes the water filter to clog more quickly. If this is the case in your area, you will have to change the filter more frequently than every six months.

(4) Lighting (Hold 3 sec for °C ↔ °F) Lighting button serves two purposes:
- To turn the dispenser light on and off

 To switch the temperature units between °C and °F
 Light Function

Touching the Lighting button turns on the Dispenser LED lamp in continuous mode so that it stays on continuously. The button also lights up. If you want the Dispenser lamp to come on only when some one uses the dispenser, press the Lighting button to turn the continuous mode off.



 To switch the temperature units between °C and °F

Touch and hold this button for 3 seconds to select the temperature display you want.

Each time you press and hold the button, the °C and °F temperature modes alternate and the °C or °F icon lights up, indicating your selection.

16_operating

DA68-02897A-06.indb 16 2014. 5. 13. 11:50

he Fridge button serves two purposes:

- To set the Fridge to your desired temperature.
- To turn the Power Cool function on and off.
- 1) To set the Fridge temperature Press the Fridge button to set the refrigerator to the temperature you want. You can set the temperature between 44°F (7°C) and 34°F (1°C).



2) Power Cool function Touch and hold this button for 3 seconds to decrease the time needed to cool products in the Refrigerator. It can be helpful if you need to quickly cool easily spoiled items or if the temperature in the fridge has warmed dramatically (For example, if the door was left open).

Ice Off (Hold 3 sec for Child Lock)

The ice Off button serves two purposes:

- To turn the loe maker on and off To turn the Child Lock Function on and off.
- 1) Ice Off Function

If you don't want to make more ice, press the Ice Off button.

2) Child Lock Function

Touch and hold this button for 3 seconds to lock the display, the Flex Zone panel, and the dispenser buttons so the buttons can not be used.



Replace the highlighted text with this text: When Child Lock is on, the refrigerator does not dispense ice, water, or sparkling water, even if the Dispenser Lever is

The Child Lock icon lights up to indicate you've activated the Child Lock function. Press 3 seconds to unlock.

(7) Cubed Ice Crushed Ice

Press the Cubed Ice or Crushed Ice button to select the type of ice you want dispensed.



(Cubed) (Crusted)

Each time you press the button, the cubed and crushed ice modes alternate and the Cubed or Crushed ice icon lights up, indicating your selection.

Ice Off

If you don't want to make more ice, touch the Ice Off button.

The icon will light up and the ice-Maker stops making ice,



- We recommend you stop ice making if the fell
 - There is enough ice in the ice bucket.
 - You want to save water and energy.
 - Water is not being supplied to the refrigerator.





If the ice maker function is ON, and there will be a water valve noise from the back of the unit. If this occurs, press the Ice Off (Hold 3sec for child lock) button for less than 3 seconds until the Ice Off indicator (21) illuminates.

To save electricity, the Panel Display turns off automatically under the following conditions: When no button has been pressed, when no doors are open, or when no Dispenser Lever has been pushed. However, the icon indicating your cubed or crushed ice selection, or sparkling water selection, will stay on. When you press a button, open a door, or push a Dispenser Lever, the Panel Display will turn on again. All function keys will become operational after you remove your finger from the button you pressed.

	(1	0)	
	F	ü	ter	

Water filter usage

This icon lights up when you need to change the filter, usually after the refrigerator has dispensed about 300 gallons of water (after about 6 months). After you install the new water filter, reset the filter indicator by touching and holding the Hold 3sec for Filter Reset button for 3 seconds.





- If water is not dispensing or dispensing slowly, you need to replace the water filter because the water filter is clogged.
- Some areas have large amounts of lime in their water, which causes the water filter to clog more quickly.

operating _17

DA68-02897A-06.indb 17 2014. 5. 13. 11:50



Cooling Off Mode

North American (US, Canada) Models Only : Cooling Off mode (also called Shop mode), is designed for use by retailers when they are displaying refrigerators on the shop floor. In Cooling Off made, the refrigerator's fan motor and lights work normally, but the compressors do not run, and the refrigerator and freezer do not get cold. To start Cooling Off mode, touch and hold the Energy Saver button and 1×1+10 the Freezer button for 5 seconds during normal operation. The refrigerator chime sounds and the temperature display flashes OFF.

To cancel Cooling Off mode, touch and

hold the Energy Saver and the Freezer

buttons again for 5 seconds.

CHANGING THE WATER FILTER

To reduce the risk of water damage warning to your property DO NOT use generic To reduce the risk of water damage brands of water filters in your SAMSUNG Refrigerator.

USE ONLY SAMSUNG BRAND WATER FILTERS. SAMSUNG is not legally responsible for any damage, including, but not limited to, property damage caused by water leakage from the use of a generic water filter. SAMSUNG Refrigerators Filter are designed to work ONLY WITH SAMSUNG Water Filters.


The Filter light turns red to let you know when it is time to change your water filter cartridge. To give you time to get a new filter, the red light comes on just before the capacity of the current filter runs out. Changing the filter on time provides you with the freshest, cleanest water from your refrigerator.



To change the water filter, follow these steps:

- 1. Shut off the water supply. Then, turn the water filter (1) about 1/4 turn, counter-clockwise.
- 2. Pull the water filter (1) from the case filter (2). To change the water filter more easily, shut off the water. shut off the water supply valve.
- · Sometimes, it is hard to disassemble the water filter because impurities in the water cause it
- 18_operating

- to stick. If you are having difficulties, grip the water filter firmly and pull it hard.
- . When you pull the water filter, a little water can leak from the opening. This is normal. To minimize the water leaks, keep the filter. cartridge horizontal when you pull it.
- To prevent overflow, empty the water filter tray (3) and dry around the filter case (2).



- 3. Insert the new filter into the filter case (4).
- 4. Push the filter, and then turn it clockwise until it locks.



- . If you have trouble inserting the water filter because of high water pressure, shut off the water supply valve.
- . The locked symbol should be lined up with the indicator line.



5. Touch the "Alarm/hold 3 sec for Filter Reset"

(1) button ((Filter Reset)) for about 3 seconds to reset the water filter. The color of



the indicator (##) changes from red to off.

6. If you turned off the water supply, turn it back



For a replacement water filter, you can visit your local home Improvement center or contact the Samsung Parts distributor. To order more water filter cartridges, contact your authorized Samsung dealer. Be sure the replacement water filter has the SAMSUNG logo on the box and on the water filter.

Removing any residual matter inside the water supply line after installing the water filter.

- 1. Turn ON the main water supply and supply water from water supply line.
- 2. Run water through the dispenser until the water runs clear (approx. 6 to



DA68-02897A-06.indb 18 2014. 5. 13. 11:50 7 minutes). This will clean the water supply system and remove air from the lines.

- Additional flushing may be required in some households.
- Open the Refrigerator door and make sure there are no water leaks coming from the water filter.



Be sure to flush the dispenser thoroughly, otherwise water may drip from the dispenser.

This means that there is still air in the line.

Reverse Osmosis Water Supply IMPORTANT:

The pressure of the water supply coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 35 and 120 psi (241 and 827 kPa).

If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa.) If the water pressure to the reverse osmosis system is less than 40 to 60 psi (276 to 414 kPa):

- Check to see whether the sediment filter in the reverse osmosis system is blocked. Replace the filter if necessary.
- Allow the storage tank on the reverse osmosis system to refill after heavy usage.
- If your refrigerator has a water filter, it may further reduce the water pressure when used in conjunction with a reverse osmosis system. Remove the water filter.

If you have questions about your water pressure, call a licensed, qualified plumber.

CONTROLLING THE TEMPERATURE

Basic temperature of Freezer and fridge compartments

The basic and recommended temperatures of the Freezer and Fridge compartments are 0°F and 37°F (or -18°C and 3°C) respectively. If the temperature of the Freezer and Fridge compartments are too high or low, adjust the temperature manually.

Controlling the Freezer temperature



Recommend Temp (Freezer): 0°F (or -18°C)

The Freezer temperature can be set between -8°F and 5°F (or between -23°C and -15°C) to suit your particular needs. Press the Freezer button repeatedly until the desired temperature is shown in the temperature display. The temperature will change by 1°F (or 1°C) with each press. See

Fahrenheit:
$$0^{\circ}F \rightarrow -1^{\circ}F \rightarrow -2^{\circ}F \rightarrow -3^{\circ}F \rightarrow -4^{\circ}F \rightarrow -5^{\circ}F \rightarrow -6^{\circ}F \rightarrow -7^{\circ}F \rightarrow -8^{\circ}F \rightarrow 5^{\circ}F \rightarrow 4^{\circ}F \rightarrow 3^{\circ}F \rightarrow 2^{\circ}F \rightarrow 1^{\circ}F \rightarrow 0^{\circ}F.$$

Keep in mind that foods like some ice cream may melt at 4"F (or -15.5"C). The temperature display will move sequentially from -8"F to 5"F (or from -23"C to -15"C).

Controlling the fridge temperature



Recommend Temp (Fridge): 37°F (or 3°C)

The fridge temperature can be set between 34°F and 44°F (or between 1°C and 7°C) to suit your particular needs. Press the Fridge button repeatedly until the desired temperature is shown

operating _19

DA68-02897A-06.indb 19 2014. 5. 13. 11:51

02 OPERATING

in the temperature display. The temperature will change by 1°F (or 1°C) with each press. See below.

Fahrenheit: 37°F → 36°F → 35°F → 34°F → 44°F + 43°F + 42°F + 41°F + 40°F + 39°F + 38°F → 37°F.

Centigrade: 3°C → 2°C → 1°C → 7°C → 6°C → 5°C → 4°C → 3°C.


The temperature control process for the Fridge works just like the Freezer process. Press the Fridge button to set your desired temperature. After a few seconds, the Fridge will begin adjusting towards the newly set temperature. This will be reflected in the digital display.



- The temperature of the Freezer or Fridge may rise when you open the doors too frequently, or if a large amount of warm or hot food is placed inside.
- A rise in temperature may cause the digital display to blink. Once the Freezer and Fridge temperature return to their normal set. temperatures, the blinking will stop.
- If the blinking continues, you may need to "reset" the Refrigerator. Try unplugging the appliance, wait for around 10 minutes and then plug the power cord back in.
- If there is a communication error between the Display and Main Controller, the Convertible Display light may blink. If the blinking continues for a long period of time, please contact a Samsung Electronics Service Center.

USING THE COLD WATER DISPENSER

Push the appropriate ice type button to select what you want dispensed.



20_operating

Using the ice lever (1)

Push the Ice lever dispenser (1) gently with your glass. Ice will be released from the dispenser. You can choose the type of ice by pushing the cubed or crushed button first.



Using the Water lever (2)

Push the Water lever dispenser (2) gently with your glass. Water will be released from the dispenser.



If you push the water and Ice lever at about the same time, the dispenser operates only the option you actually selected or pushed first.



Please wait 1 second before removing the cup after dispensing water to prevent spills. Do not pull out the lever dispenser after dispensing ice or water. It comes back automatically.

Using the Ice & Water Dispenser

To get Ice and water, push the Ice lever (1) first for ice, then move your glass down and press the water dispenser lever (2) for water.


Maintaining the Ice Bucket

- . To clean the ice bin/bucket, wash with a mild detergent, rinse well, and dry thoroughly it. Do not use harsh or abrasive cleaners or solvents.
- · Ice is made in cubes. When you select "Crushed", the ice maker grinds the ice cubes into crushed ice.
- · When you select Cubed Ice after using the Crushed Ice mode, a small amount of residual crushed ice might be produced.
- The ice cubes generated by the rapid ice making process will look white, which indicates they were generated normally.
- · As the ice maker in the refrigerator room makes ice cubes even faster, move the ice cubes from the refrigerator ice bin to the freezer ice bin if you need more ice cubes.
- . If ice doesn't come out, pull out the ice bucket and press the test button located on the right. side of ice maker. See the illustration below.
- · Do not press the test button continuously when the tray is filled with ice or water. Water may overflow or ice may jam the bucket.

DA68-02897A-06.indb 20 2014. 5. 13. 11:51


Making Ice

- . To fill the ice bucket to maximum capacity after installation, follow these steps:
- 1. Allow your refrigerator to operate and cool down for 24 hours (or 1 full day).
- Waiting 24 hours will allow your ice maker to cool properly.



- 2. Dispense 4 to 6 ice cubes into the glass.
- 3. After 8, and then 16 hours, dispense a full glass of ice.
- · To test the ice maker, press the Test button on the ice maker. You will hear the refrigerator chime (ding-dang). When the chime sounds, release the Test button.
- · The chime sounds automatically again to let you know the ice maker is working well.

you want to remove the ice cubes without using the ice bucket, please turn the ice maker off and remove the ice maker's front cover from the ice maker. Note that the ice cubes in the ice maker can spill out over the drawer.



Note that the ice cubes in the ice bucket CAUTION May spill out over the drawer when you remove the ice bucket from the drawer. If this occurs, be sure to clear the ice cubes that spilled out of the drawer.

If a power failure occurs, ice cubes may CAUTION melt, and then freeze together when the power comes back on, causing the dispenser to stop working.







To prevent this problem, after a power failure, pull out the ice bucket and discard the residual ice or

If you use all the ice at once, you must repeat ice making Steps 2 and 3, left, However, only wait 8 hours before dispensing the first 4 to 6 ice cubes. This will replenish the ice cubes and ensure maximum ice production.

Using the Ice Off Function

When you select the Ice Off mode, remove all ice cubes from the bucket. If you leave the ice cubes in the bucket, the ice cubes may clump together, making it difficult to remove them. To remove the ice bucket, push the button on the upper right of the bucket (1 in the illustration above), lift up the bottom, and then pull out. To put the bucket back in, push the bucket straight back until you hear a click. If the bucket does not fit, turn the helix 90 degree (see the last illustration on the right, above) and try again.



- . Use only the ice maker provided with the Use only the caution refrigerator.
 - · Have a suitably qualified person install and connect the water supply line to the refrigerator.
 - . Connect the water supply line to a potable water supply only.
 - . To operate the ice maker properly, water pressure of 20 - 125 psi (138 - 862 kPa)is required.

Going on vacation...

If you have a long vacation or business trip and won't use the water or ice dispensers for a long

- Close the water valve. Otherwise, water leakage may occur.
- Remove all food.
- Unplug the refrigerator.
- Wipe excess moisture from inside and leave the doors open. Otherwise, odor and mold may develop.

Ice Maker Do's and Don'ts

- . Do not put your fingers, hands or any other unsuitable objects in the chute or ice-maker
- It may result in personal injury or material damage.

operating _21

DA68-02897A-06.indb 21 2014. 5. 13. 11:51



- · Never put your finger or any other objects in the dispenser opening.
- It may cause injury.
- . Do not try to disassemble the ice maker.
- . Do not wash or spray the ice bucket with water while it is in the refrigerator. Remove it to clean it



When you insert the loe maker tray, be caution sure that the tray is well centered at the entrance.

Otherwise, the tray may get stuck.

Water clouding phenomenon




All water provided to the refrigerator flows through the core filter which is an alkaline water filter. In the filtering process, the pressure of the water that has flowed out of the filter is increased, and the water becomes saturated with oxygen and nitrogen. When this water flows out into the air, the pressure plummets and the oxygen and nitrogen get supersaturated, which results in gas bubbles. The water may temporarily look misty or cloudy due to these oxygen bubbles. After a few seconds, the water will look clear.

22_operating

DA68-02897A-06.indb 22 2014. 5. 13. 11:51

PARTS AND FEATURES

Review the illustration below to become more familiar with the parts and features of your refrigerator.





When closing the door, make sure the Vertical Hinged Section is in the correct position to avoid scratching the other door.

If the Vertical Hinged Section is reversed, put it back to the right position and close the door. Moisture may appear at times on the Vertical Hinged Section.

The door handle may become loose over time. If this happens, tighten the bolts found on the

If you close one door with too much force, the other door may open.



When the door opens, the interlock switch automatically turns off the auger motor in the ice maker for safety reasons.




If the interior or exterior LED lamp has gone out, please contact your service agent.

operating _23


DA68-02897A-06.indb 23 2014. 5. 13. 11:51

USING FLEX ZONE

The Flex Zone is a full-width drawer with an adjustable temperature control. You can use the Flex Zone for large party trays, deli items, wines, pizzas, beverages, or miscellaneous items. There is a temperature sensor which lets you adjust the amount of cold air allowed into the Zone. The control buttons are located on the cap door center.



Temperature Selection Button



- · Press the Temp button repeatedly until your desired mode is lit.
- · Each time you press the Temp button, you change the mode in this order: Meat/ Fish mode (29°F(-1°C)), Cold Drinks mode (33°F(1°C)), Deli/Snack mode (37°F(3°C)), Wine/Party Dishes mode (42°F(5°C)). Initially, the Cold Drinks mode is selected. The refrigerator will adjust the temperature in the Flex Zone automatically to the temperature you selected.
- · The Flex Zone Temp. Display may change depending on the number of items inside, where they are located, the ambient temperature, and how often the door is opened.

Selection Button

- 1. When "Wine/Party Dishes" is selected, the temperature of the Flex Zone will be kept around 42°F (5°C). This feature helps keep food fresh for a long time.
- 2. When "Deli/Snack" is selected, the temperature of the Flex Zone will be kept around 37°F (3°C). This feature helps keep food fresh for a longer time.
- 3. When "Cold Drink" is selected, the temperature of the Flex Zone will be kept around 33°F (1°C). This feature helps keep drinks cold and refreshing.
- 4. When "Meat/Fish" is selected, the temperature of the Flex Zone will be kept around 29°F (-1°C). This feature helps keep meat or fish fresh for a longer time.

Examples of food items you can store in the Flex Zone by temperature setting.

Wine Party Dishes	Deli Snacks	Cold Drinks	Meat Fish	
• wine	 pineapples 	 bottled water 	steaks	
 cockta 	ils • lemons	• juice	 cold cuts 	
 cakes 	 biscuits 	 soft drinks 	 bacon 	
 chees 	es • potatoes	• beer	 chili dogs 	



Fruit and vegetables may be damaged if stored under the "Meat Fish" setting. Do not store lettuce or other leafy produce in the Flex Zone.



Do not store glass bottles in the Flex Zone Do not store glass posses, or "Meat/Fish" setting. If they are frozen, they can break and cause personal injury.


RECOMMENDED LOCATION FOR THE FOLDABLE SHELF

The Foldable Shelf folds up from the center, giving you more storage area for tall items without your having to re-arrange the shelves.

- . Install the Foldable Shelf on the right side of the refrigerator.
- . If you install the Foldable Shelf on the left side, the ice maker will prevent the shelf from folding
- . To use, push the front portion of the shelf back gently so that the shelf folds up from the

24 operating

DA68-02897A-06.indb 24 2014. 5. 13. 11:51



REMOVING THE REFRIGERATOR ACCESSORIES

1. Door Bins

. Door Bins (1)

To remove - Simply lift the bin up and pull straight out.

To relocate - Slide it in above the desired location and push down until it stops.

· Door Bins (2)

To remove - Take the right side of the bin out by lifting it at an angle along the guide, and then take the left side out by pulling it from the door.

To relocate - Slide it into the original location and push down until it sticks.

Injuries can occur if the door bins are not firmly connected to the doors.


Do not allow children to play with the bins. Sharp corners of the bins may cause injury.

Do not adjust a bin full of food. Remove caution the food first.

To remove dust from the bins, remove the guard and wash in water.


2. Tempered Glass shelves

To remove - Tilt up the front of the shelf in the direction shown (1) and lift it up vertically (2).



Pull the shelf out.

To re-install - Tilt the front of the shelf up and guide the shelf hooks into the slots at a desired height. Then lower the front of the shelf so that the hooks can drop into the slots.



The Tempered Glass shelves are heavy. CAUTION Use special care when removing them.

3. Foldable Shelf

To remove - After removing the Shelf Front, lift up the Shelf and remove it.


To re-install - Hook the Shelf on the Angle Frame and re-attach the Shelf Front to the Foldable Shelf.





After sliding the foldable shelf in and caution folding it, the Shelf Front can be removed for your convenience. If you use the self without removing, be careful of its possible separation.

4. Vegetable & Fruit Drawers



operating _25


DA68-02897A-06.indb 25 2014. 5. 13. 11:51

To remove

· Simply lift the bin up and pull straight out.



 Tilt up the front of the drawer and pull straight out, and pull out the drawer after moving slightly in the direction of the arrow.



To re-install


- Insert the drawer into the frame rails and push back into place.
- Slide bin in above the desired location and push down until it stops.

The drawers need to be removed before caution the glass shelf above them can be lifted out.

5. Flex Zone

To remove the Flex Zone – Pull the Flex door out to full extension. Lift the Flex Zone up, pulling it to your body with both hands.

To re-install the Flex Zone – Open the Flex door to full extension. Tilt the front of the Flex Zone up, place the back of the Flex Zone onto the rails, and then lower the front until the whole Zone rests on the rails.



When the Flex Zone or LED lighting is not working, check the connectors [(1), (2) shown below] for cracks or leaks.

26_operating



- 1. Refer to page 12 for disassembly instructions.
- Open the cap cover rail with a flat-blade screwdriver.

Using the doors

Ensure that the doors close all the way and are securely sealed.

When the refrigerator door is only partially open, it will automatically close. If the the door is opened more than its auto close range, it will remain open. You must close if manually.

REMOVING THE FREEZER ACCESSORIES

1. Freezer Room Guard

To remove - Remove the freezer room guard (1) by lifting the guard up.

To re-install - Push down until the guard (1) locks into place.



2. Super Extended Drawer

To remove - Pull the drawer out to full extension. Tilt up the rear of the drawer and lift straight out.

DA68-02897A-06.indb 26 2014, 5, 13. 11:51

To re-install - Place the drawer onto the rails (4) by tilting it up. Lower the drawer into place until it is horizontal and slide the Drawer (3) in.



3. Freezer Drawer

To remove the freezer drawer - Pull the freezer drawer out fully. Tilt up the rear of the bin and lift it out to remove.

To re-install the freezer drawer - Place the bin into the rail assembly.



You can scratch the side of the bin if you You can scratch the side of the oin if you cannot twist it left or right when disassembling or re-assembling it.




Do not allow babies or children go inside caution the freezer drawer. They could damage the refrigerator and seriously injure themselves. Do not sit on the freezer door. The door may break. Do not allow children to climb into the freezer drawer.



CAUTION Do not remove the divider.



If trapped inside, children may be injured warning or suffocate to death.




CLEANING THE REFRIGERATOR

Caring for your Samsung French Door Refrigerator prolongs its life and helps keep it free of odor and germs.

Cleaning the Interior

Clean the inside walls and accessories with a mild detergent and then wipe dry with a soft cloth. You can remove the drawers and shelves for a more thorough cleaning. Just make sure to dry drawers and shelves before putting them back into place.



Cleaning the Exterior

Wipe the control panel and digital display with a damp, clean, soft cloth. Do not spray water directly on the surface of the refrigerator. The doors, handles, and cabinet surfaces should be cleaned with a mild detergent and then wiped dry with a soft cloth. To keep your appliance looking its best, polish the exterior once or twice a



Do not spray water directly on the Do not spray water directly on the caution refrigerator. Use a clean, damp cloth to clean.



Do not use benzene, thinner, or Clorox for cleaning. They may damage the surface of the appliance and may cause a fire.



You can erase the printed You can erase the printed caution letters on the display if you apply stainless cleaner directly to the area where the letters are printed.



operating _27

DA68-02897A-06.indb 27 2014. 5. 13. 11:51



Cleaning the Ice / Water Dispenser

Push down one end of the tray dispenser and remove it. Wipe the Ice / Water Dispenser with a clean, soft cloth.



When using the crushed ice caution selection from the dispenser some residual ice chips may start to collect in the ice chute. To prevent that residual ice from melting and running out of the chute, you should clean out the residual ice when you see it start to collect in the ice chute.



Cleaning the Rubber door seals

If the rubber door seals are dirty, the doors may not close properly, and the refrigerator will not operate efficiently. Keep the door seals free of dust or stains by cleaning the doors using a mild detergent and damp cloth. Wipe dry with a clean, soft cloth.






Do not clean the refrigerator with benzene, Do not clean the refrigerator with caution thinner, or car detergent. These substances could cause a fire.

Cleaning the rear side of the refrigerator

To keep cords and exposed parts free of dust and dirt accumulation, vacuum the rear side of the appliance once or twice a year.





28_operating

DA68-02897A-06.indb 28 2014. 5. 13. 11:51

FOOD STORAGE TIPS

Foods	Refrigerator	Freezer	Storage Tips
DAIRY PRODUCTS	:	***	11
Butter	2-3 Weeks	6-9 Months	Wrap or cover tightly.
Milk	1-2 Weeks	Not recommended	Check date code. Most milk and similar prod- ucts are sold in date-coded cartons that indicate a products is peak freshness. Re-seal with cap or wrap tightly. Do not return unused portions to original container.
Cream Cheese, cheese food, and cheese spread	2-4 Weeks	Not recommended	
Hard Cheese (unopened)	3-4 Months	6 Months	Check date code. Keep all cheese tightly packed
Hard Cheese (opened)	2 Months	Not recommended	in moisture proof wrap
Cottage Cheese	10-15 Days	Not recommended	
Cream	7-10 Days	2 Months	Check date code. Most yogurt, creams, and
Sour Cream	2 Weeks	Not recommended	similar products are sold in date-coded cartons that indicate a product's peak freshness. Re-seal
Cream Dips (opened)	1 Week	Not recommended	or cover tightly. Do not return unused portions to original container.
Yogurt	10-14 Days	Not recommended	
Frazen Yogurt	na	2 Months	Check date code. Keep covered.
EGGS		50	V.
Eggs (uncooked)	3-4 Weeks	Not recommended	Check date code. Store eggs in coldest part of refrigerator and in their original container.
Eggs (cooked)	1 Week	Not recommended	Store in covered container
Leftover egg dishes	3-4 Days	Not recommended	Store in covered container
FRESH FRUITS		N	
Apples	1 Month	Not recommended	
Banarias	2-4 Days	Not recommended	
Peaches, Melons, Pears, Avocados	3-5 Days	Not recommended	If storing in refrigerator, do not wash fruit before
Berries and Chemies	2-3 Days	12 Months	storing. Store in moisture resistant bags or
Apricots	3-5 Days	Not recommended	 containers. Wrap cut fruits; Some fruits darken when refrigerated.
Grapes	2-5 Days	na	
Pineapple (un-cut)	2-3 Days	Not recommended	
Pineapple (cut)	5-7 Days	6-12 Months]
Citrus	1-2 Weeks	Not recommended	Store uncovered.
Juice	6 Days	Not recommended	Check date code and re-seal in original con- tainer. Do not return unused portions to original container.
Frozen Juice	Thawing only	12 Months	Check date code. Do not re-freeze.

operating _29

DA68-02897A-06.indb 29 2014. 5. 13. 11:51

Foods	Refrigerator	Freezer	Storage Tips	
FISH AND SHELLF	ISH	7.0	- N	
Fish	96	901	200	
Fatty Fish (mack- erel, trout, salmon)	1-2 Days	2-3 Months	Keep in original wrapper and store in coldest part of refrigerator. Package in vapor-proof and moisture	
Lean Fish (cod, flounder, etc)	1-2 Days	6 Months	proof wrap for freezer. Freeze at 0°F (or -18°C). Thaw in refrigerator or check date code. Freeze in original	
Frozen or Breaded	na	3 Months	packaging.	
Shellfish		965	#0 #0	
Shrimp (uncooked)	1-2 Days	12 Months		
Crab	3-5 Days	10 Months	To freeze, package in vapor-proof and moisture-proof	
Cooked Fish or Shellfish	2-3 Days	3 Months	container.	
MEAT	7:	- AV		
Fresh, Uncooked				
Chops	2-4 Days	6-12 Months		
Ground	1 Day	3-4 Months	7	
Roast	2-4 Days	6-12 Months	Check date code for use. Store in coldest part of	
Bacon	1-2 Weeks	1-2 Months	 refrigerator in original packaging. Package in moisture proof and vapor-proof container for freezing. Recom- 	
Sausage	1-2 Days	1-2 Months	mended refrigerator temperature 33°F to 36°F (or 1°C to 2°C) and freezer temperature 0°F to 2°F (or -18°C	
Steak	2-4 Days	6-9 Months	to -16°C)	
Poultry	1 Day	12 Months		
Lunch meat	3-5 Days	† Month		
Cooked	100			
Meat	2-3 Days	2-3 Months	Check date code for use. Store in coldest part of	
Poultry	2-3 Days	4-5 Months	refrigerator in original packaging. Package in moisture	
Ham	1-2 weeks	1-2 Months	proof and vapor-proof container for freezing.	

Sources:

American Meat Institute Foundation. 1994. Yellow pages; answers to predictable questions consumers ask about meat and poultry. American Meat Institute Food Marketing Institute. 1999. The food keeper. Food Marketing Institute, Washington, D.C. Freeland-Graves, J.H. and G.C. Peckham. 1996. Foundations of food preparation, 6th ed. Prentice-Hall, Inc. Englewood Ciffs, NJ. Hillers, V.N. 1993. Storing foods at home. Washington State University Cooperative Extension, Pullman, WA. Publ. EB 1205.

National Restaurant Association. 2001. Be cool-chill out! Refrigerate promptly. National Restaurant Association Education Foundation/4s International Food Safety Council, Washington, D.C. USDA. 1997. Basics for handling food safely. U.S. Department of Agriculture, Food Safety and Inspection Service, Washington, D.C.

30_ operating

DA68-02897A-06.indb 30 2014. 5. 13. 11:51

03 TROUBLESHOOTING

Troubleshooting

PROBLEM	SOLUTION	
The refrigerator does not work at all or it does not chill sufficiently.	Check that the power plug is properly connected. Check if the set temperature on the digital display is warmer than the freezer or fridge inner temperature. If it is, set the refrigerator colder. Is the refrigerator in direct sunlight or located near a heat source? Is the back of the refrigerator too close to the wall, preventing proper ventilation?	
The food in the fridge is frozen.	Check if the set temperature on the digital display is too low. Try setting the refrigerator to a warmer temperature. Is the temperature in the room too low? Set the refrigerator warmer. Did you store the food which is juicy in the coldest part of the refrigerator? Try moving those items to the other shelves in the fridge instead of keeping them in the colder areas or bins.	
You hear unusual noise or sounds.	Check that the refrigerator is level and stable. Is the back of the refrigerator too close to the wall, preventing proper ventilation? Try moving the back of the refrigerator at least 2 inches from the wall. Was anything dropped behind or under the refrigerator? A "ticking" sound is heard from inside the refrigerator. It is normal and occurs because various accessories are contracting or expanding according to the temperature of the refrigerator interior. If it sounds as if something is hitting something else inside the refrigerator, this is normal. The sound is caused by the compressor operating at high	
The cabinet- door sealing area of the appliance is hot and condensation is occurring.	Some heat is normal as anti-condensators are installed in the vertical hinged section of the refrigerator to prevent condensation. Is the refrigerator door ajar? Condensation can occur when you leave the door open for a long time.	
Ice Maker is not producing ice.	Did you wait for 12 hours after installing the water supply line before making ice? Is the water line connected and the shut-off valve opened? Did you manually stop the ice making function? Is the freezer temperature too warm? Try setting the freezer temperature lower.	
You can hear water bubbling in the refrigerator.	This is normal. The bubbling comes from refrigerant circulating through the refrigerator.	
There is a bad smell in the refrigerator.	Check for spoiled food. Foods with strong odors (for example, fish) should be tightly covered. Clean out your freezer periodically and throw away any spoiled or suspicious food.	

Troubleshooting _31

DA68-02897A-06.indb 31 2014. 5.13. 11:51

PROBLEM	SOLUTION		
Frost forms on the walls of the freezer.	Is the air vent blocked? Remove any obstructions so air can circulate freely. Allow sufficient space between the stored food for efficient air circulation. Is the freezer drawer closed properly?		
Water dispenser is not functioning,	Is the water line connected and the shut-off valve opened? Has the water supply line tubing been crushed or kinked? Make sure the tubing is free and clear of any obstruction. Is the water tank frozen because the fridge temperature is too low? Try selecting a warmer setting on the Digital display. Is the Child Lock on?		
Auto close system does not work with the freezer door.	Is there an imbalance between the right and left parts of the door? Open and close the door smoothly 1–2 times. After you do this, the auto close system usually works properly again. Try opening the door smoothly to avoid unbalancing the right part and the left part of the door.		
Condensation or water drops forms on both sides of fridge door's central part.	Condensation or water drops may form if the humidity is too high while the refrigerator is operating. If condensation or water drops appears on both sides of fridge door's central part, turn the Energy Saver mode off after removing the condensation. (See the explanation on Energy Saver button in the USING THE CONTROL PANEL.)		

32_Traubleshooting

DA68-02897A-06.indb 32 2014. 5. 13. 11:51

Warranty (USA)

WARRANTY ON SAMSUNG REFRIGERATOR

LIMITED WARRANTY TO ORIGINAL PURCHASER

This Samsung brand product, as supplied and distributed by Samsung Electronics America, Inc. (Samsung) and delivered new, in this original carton to the original consumer purchaser, is warranted by Samsung against manufacturing defects in materials and workmanship for a limited warrantly period of:

One (1) year Parts and Labor on Refrigerator

Five (5) years Parts and Labor on sealed Refrigeration system only*

Ten (10) years Parts and Five (5) years Labor on Digital Inverter Compressor

("Compressor, evaporator, condenser, drier, connecting tubing)

This limited warranty begins on the original date of purchase, and is valid only on products purchased and used in the United States. To receive warranty service, the purchaser must contact Samsung for problem determination and service procedures. Warranty service can only be performed by a Samsung authorized service center. The original dated bill of sale must be presented upon request as proof of purchase to Samsung or Samsung authorized service center.

Samsung will repair or replace any part found to be defective, at our option and at no charge as stipulated herein, with new or reconditioned parts during the limited warranty period specified above. All replaced parts and products become the property of Samsung and must be returned to Samsung. Replacement parts and products assume the remaining original warranty, or ninety (90) days, whichever is longer.

In-home service will be provided during the warranty labor period subject to availability within the contiguous United States. In-home service is not available in all areas. To receive in-home service, the product must be unobstructed and accessible from floor level to service personnel. If during in-home service repair cannot be completed, it may be necessary to remove, repair and return the product. If in-home service is unavailable, Samsung may elect, at our option, to provide for transportation of our choice to and from a Samsung authorized service center. Otherwise, transportation to and from the Samsung authorized service center is the responsibility of the nurchiser.

This limited warranty covers manufacturing defects in materials and workmanship encountered in normal, noncommercial use of this product, and shall not apply to the following, including, but not limited to: damage which occurs in shipment; delivery and installation; applications and uses for which this product was not intended; altered product or serial numbers; cosmetic damage or exterior finish; accidents, abuse, neglect, fire, water, lightning or other acts of nature; use of products, equipment, systems, utilities, services, parts, supplies, accessories, applications, installations, repairs, external plumbing and leaks; external wring, circuit breakers, fuses or connectors not supplied and authorized by Samsung, or which damage this product or result in service problems; incorrect electrical line voltage, fluctuations and surges; customer adjustments and failure to follow operating instructions, cleaning, maintenance and environmental instructions that are covered and prescribed in the instruction book; loss of food due to spoilage; consumable items including filters and light.

THERE ARE NO EXPRESS WARRANTIES OTHER THAN THOSE LISTED AND DESCRIBED ABOVE, AND NO WARRANTIES WHETHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, SHALL APPLY AFTER THE EXPRESS WARRANTY PERIODS STATED ABOVE, AND NO OTHER EXPRESS WARRANTY OR GUARANTY GIVEN BY ANY PERSON, FIRM OR CORPORATION WITH RESPECT TO THIS PRODUCT SHALL BE BINDING ON SAMSUNG. SAMSUNG SHALL NOT BE LIABLE FOR LOSS OF REVENUE OR PROFITS, FAILURE TO REALIZE SAVINGS OR OTHER BENEFITS, OR ANY OTHER SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES CAUSED BY THE USE, MISUSE OR INABILITY TO USE THIS PRODUCT, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED, AND EVEN IF SAMSUNG HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. NOR SHALL RECOVERY OF ANY KIND AGAINST SAMSUNG BE GREATER IN AMOUNT THAN THE PURCHASE PRICE OF THE PRODUCT SOLD BY SAMSUNG AND CAUSING THE ALLEGED DAMAGE. WITHOUT LIMITING THE FOREGOING, PURCHASER ASSUMES ALL RISK AND LUBBLITY FOR LOSS, DAMAGE OR INJURY TO PURCHASER AND PURCHASER SPROPERTY AND TO OTHERS AND THEIR PROPERTY ARISING OUT OF THE USE, MISUSE OR INABILITY TO USE THIS PRODUCT SOLD BY SAMSUNG NOT CAUSED DIRECTLY BY THE NEGLIGENCE OF SAMSUNG. THIS LIMITED WARRANTY SHALL NOT EXTEND TO ANYOND OTHER THAN THE ORIGINAL PURCHASER OF THIS PRODUCT SOLD BY SAMSUNG OF THEIR THAN THE ORIGINAL PURCHASER

Some states do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. To obtain warranty service, please contact Samsung at:

SAMSUNG CUSTOMER CARE CENTER

Samsung Bectronics America, Inc. 85 Challenger Road Ridgefield Park, NJ 07660 1-800-SAMSUNG (1-800-726-7864) and www.samsung.com

DA68-02897A-06.indb 33 2014. 5. 13. 11:51

In case the need for servicing arises

Do not hesitate to call any Samsung Authorized Service Center nearby giving them your name, address and telephone number when your product is not functioning properly.

Warranty Information (CANADA)

Limited Warranty for Original Purchaser

This Samsung product is warranted by Samsung Electronics Canada Inc. (hereafter referred to as SECA) against manufacturing defects in material or workmanship for the following periods:

> Labor: 1 years (in-home) Parts: 1 years Inverter Compressor: 10 years

SECA further warrants that if this product fails to operate properly within the specified warranty period and the failure is due to improper workmanship or defective material, SECA will repair or replace the product at its option. In-home service is not available in all areas. Contact us to find out if in-home service is currently available in your area by using the contact information at the back of this warranty.

All warranty repairs or part replacements must be performed by a SECA Authorized Service Center. (To find the nearest SECA Service Center, call 1-800-SAMSUNG (7267864) or visit our web site at www.samsung.com/ca)

Obligation to the Original Owner

The original dated sales receipt must be retained by the customer and is the only acceptable proof of purchase, it must be presented to a SECA Authorized Service Center at the time service is requested before warranty services are rendered. On all carry-in models, transportation to and from the Authorized Service Center is the responsibility of the customer.

Exclusions of the Warranty

This warranty does not cover damage due to accident, fire, flood, and/or other Acts of God, misuse, incorrect line voltage, improper installation, improper or unauthorized repairs, commercial use, or damage that occurs during shipping. Customer adjustments which are explained in this owners manual are not covered under the terms of this warranty. This warranty will automatically be voided for any unit found with a missing or altered serial number.

This warranty is valid only on products purchased and used in the Canada.

Samsung Electronics Canada Inc. 2050 Derry Road West, Mississauga, Ontario L5N 0B9 Canada

Customer Care Center 1-800-SAMSUNG (726-7864) Customer Care Center Fax. 1-866-436-4617

If you have any questions or comments relating to Samsung products, please contact the SAMSUNG customer care center.

Semsung Electronics Canada Inc. 2050 Derry Road West, Mississauga, Ontario L5N 089 Canada TEL: 905-542-3535 FAX: 905-542-3835 1-800-SAMSUNG (726-7864) www.samsung.com/us/support

DA68-02897A-06.indb 34 2014. 5. 13. 11:51

memo

DA68-02897A-06.indb 35 2014. 5. 13. 11:51





Contact SAMSUNG WORLD WIDE

If you have any questions or comments relating to Samsung products, please contact the SAMSUNG customer care center.

Country	Contact Center	Web Site	Subsidiaries office address
U.S.A	1-800-SAMSUNG (726-7864)	www.samsung.com/us/support	Samsung Electronics America, Inc. 85 Challenger Road Ridgefield Park, NJ 07660
CANADA	1-800-SAMSUNG (726-7864)	www.samsung.com/ca/support (English) www.samsung.com/ca_f/support (French)	Semaung Electronics Canada Inc. 2050 Derry Road West, Mississauga, Ontario L5N 089 Canada

DA68-02897A-06.indb 36 2014. 5. 13. 11:51