MUELLER[®] A-3[™] DRILLING & TAPPING MACHINE (39210)

Mueller A-3 Machine - for drilling, tapping and inserting operations under pressure - 1" to 2-1/2" inclusive

- Catalog number A-3
- □ Hand or power operation
- Designed for use on pressurized or dry mains
- □ Insert or extract corporation stops from 1" to 2" and pipe plugs to 2-1/2" in size
- Use on cast iron or ductile iron pipe cement lined cast iron or ductile iron pipe
 A-C pipe cast iron O.D. PVC steel pipe
- 90 psig (621 kPa) maximum working pressure without optional power clevis
- 200 psig (1379 kPa) maximum working pressure with optional power clevis
- 250 F (121 C) maximum working temperature



Equipment furnished with each machine (For part numbers see page 1.17):

- □ Wooden storage chest (not shown)
- Ratchet handle
- Ratchet handle extension
- Small saddle gasket (fits between machine and saddle)
- □ Large saddle gasket (fits between saddle and pipe)
- □ Flat link chain with eyebolt and nut for 6" thru 16" pipe
- Chain hook, nut and washer
- Box end wrench for chain hook nut
- Allen wrench
- Open end corporation stop wrench
- Body cleaning chisel (for cleaning debris from inside of machine body)
- Cutting grease
- □ Instruction manual (Form #8541)

Equipment to be selected:

- Combined drills and taps or shell cutters and taps—page 1.12 and 1.13
- Inserting tools (used to insert corporation stops or pipe plugs)—page 1.14

Mueller Co.

 Machine saddles (adapts machine to specific type and size of main)—page 1.15

Optional equipment:

- o Extracting tools (used to remove corporation stops or pipe plugs)—page 1.14
- o Equipment for special uses---1.16
- o Power operators-page 1.25

	A-3
Total shipping weight	188 lbs. (85 kg)
Handling weight during operation - Upper section	40 lbs. (18 kg)
Handling weight during operation - Lower section	58 lbs. (26 kg)
Shipping length	36"
Extended length	54"