

STANDARD FITTINGS

No. 10 – 90° Elbow
 No. 11 – 45° Elbow
 No. 12 – 22½° Elbow




No. 10 – 90° Elbow


No. 13 – 11¼° Elbow
 No. 100 – 90° Long Radius Elbow
 No. 110 – 45° Long Radius Elbow



No. 11 – 45° Elbow



No. 12 – 22½° Elbow



No. 13 – 11¼° Elbow



No. 100 – 90° Elbow



No. 110 – 45° Elbow


Size		No. 10 90° Elbow	No. 11 45° Elbow	No. 12 22½° Elbow (sw)	No. 13 11¼° Elbow (sw)	No. 100† 90° Long Radius Elbow (S)	No. 110† 45° Long Radius Elbow (S)
Nominal Size inches or mm	Actual Pipe Outside Diameter inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm
¾	1.050 26.9	2.25 57	1.50 38	1.63 sw 41	1.38 sw 35	—	—
1	1.315 33.7	2.25 57	1.75 44	3.25 @ 83	1.38 sw 35	—	—
1¼	1.660 42.4	2.75 70	1.75 44	1.75 44	1.38 sw 35	—	—
1½	1.900 48.3	2.75 70	1.75 44	1.75 44	1.38 sw 35	—	—
2	2.375 60.3	3.25 83	2.00 51	3.75 @ 95	1.38 35	4.38 111	2.75 70
2½	2.875 73.0	3.75 95	2.25 57	4.00 @ 102	1.50 38	5.13 130	3.00 76
76.1 mm	3.000 76.1	3.75 95	2.25 57	2.24 57	1.50 38	—	—
3	3.500 88.9	4.25 108	2.50 64	4.50 @ 114	1.50 38	5.88 149	3.38 86
3½	4.000 101.6	4.50 114	2.75 70	2.50 sw 64	1.75 sw 44	—	—
4	4.500 114.3	5.00 127	3.00 76	2.88 73	1.75 44	7.50 191	4.00 102
108.0 mm	4.250 108.0	5.00 127	3.00 76	—	—	—	—
4½	5.000 127.0	5.25 sw 133	3.13 sw 79	3.50 89	1.88 sw 48	—	—
5	5.563 141.3	5.50 140	3.25 83	2.88 sw 73	2.00 sw 51	+	+
133.0 mm	5.250 133.0	5.50 140	3.25 83	—	—	—	—
139.7 mm	5.500 139.7	5.50 140	3.25 83	2.87 73	2.00 51	—	—
6	6.625 168.3	6.50 165	3.50 89	6.25 @ 159	2.00 51	10.75 273	5.50 140
159.0 mm	6.250 159.0	6.50 165	3.50 89	—	—	—	—




Always refer to the current Victaulic submittal publication in the G-100 General Catalog or on the website www.victaulic.com for the most up-to-date dimensional information.




STANDARD FITTINGS




No. 10 – 90° Elbow




No. 11 – 45° Elbow



No. 12 – 22½° Elbow



No. 13 – 11¼° Elbow



No. 100 – 90° Elbow



No. 110 – 45° Elbow

Size		No. 10 90° Elbow	No. 11 45° Elbow	No. 12 22½° Elbow (sw)	No. 13 11¼° Elbow (sw)	No. 100† 90° Long Radius Elbow (S)	No. 110† 45° Long Radius Elbow (S)
Nominal Size inches or mm	Actual Pipe Outside Diameter inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm	C to E inches/mm
165.1 mm	6.500 165.1	6.50 165	3.50 89	3.13 79	2.00 51	10.75 273	5.50 140
8	8.625 219.1	7.75 197	4.25 108	7.75 @ 197	2.00 51	14.25 362	7.25 184
10	10.750 273.0	9.00 229	4.75 121	4.38 sw 111	2.13 sw 54	15.00 381	6.25 159
12	12.750 323.9	10.00 254	5.25 133	4.88 sw 124	2.25 sw 57	18.00 457	7.50 191
14 #	14.000 355.6	14.00 355.6	5.75 146	5.00 sw 127	3.50 sw 89	21.00 s 533	8.75 s 222
377.0 mm †	14.843 377.0	14.84 376.9	6.15 156.2	—	—	—	—
16 #	16.000 406.4	16.00 406.4	6.63 168	5.00 sw 127	4.00 sw 102	24.00 s 610	10.00 s 254
426.0 mm †	16.772 426.0	16.77 426.0	6.95 176.5	—	—	—	—
18 #	18.000 457.0	18.00 457.2	7.46 189	5.50 sw 140	4.50 sw 114	27.00 s 686	11.25 s 286
480.0 mm †	18.898 480.0	18.90 480.0	7.83 198.8	—	—	—	—
20 #	20.000 508.0	20.00 508.0	8.28 210	6.00 sw 152	5.00 sw 127	30.00 s 762	12.50 s 318
530.0 mm †	20.866 530.0	20.87 530.0	8.64 219.4	—	—	—	—
24 #	24.000 610.0	24.00 609.6	9.94 252	7.00 sw 178	6.00 sw 152	36.00 s 914	15.00 s 381
630.0 mm †	24.803 630.0	24.80 630.0	10.27 261.0	—	—	—	—
14 – 24	AGS For AGS fitting information, refer to the AGS fittings section.						

@ Gooseneck design, end-to-end dimension

For use on cut-grooved systems only. For roll grooved systems, Victaulic offers the Advanced Groove System (AGS).

† Chinese standard sizes

NOTE: All fittings are ductile iron unless noted otherwise with an “sw” or “s”.
SW = Segmentally Welded, S = Carbon Steel



Always refer to the current Victaulic submittal publication in the G-100 General Catalog or on the website www.victaulic.com for the most up-to-date dimensional information.

