PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192



PART NUMBER:	54502
DESCRIPTION:	12 AWG SOLID UF/TWU CABLE
CONSTRUCTION:	This cable consists of one bare copper insulated conductor.
APPROVALS:	UL Standard 493, CSA 22.2 No.75
APPLICATION:	Underground Feeder Cable for Direct Burial Applications

Construction Parameters:

Conductor Stranding Insulation Material Insulation Thickness Insulated Conductor Diameter Number of Conductors 12 AWG Bare Copper Solid PVC 0.061" Nom. 0.203" Nom. 1

Electrical & Electrical Properties:

Temperature Rating
Operating Voltage
DC Resistance per Conductor @ 20 ⁰ C

-20^oC to 60^oC 600 V RMS Max. 1.59 Ohms/1M' Nom.

Insulation Colors

Various

Legend (Surface Ink Print)

BARON WIRE E61390 12 AWG (3.31mm²) (UL) TYPE UF 600V -- C(UL) TWU 60C FT1 yyddd

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name_____Customer Approval _____

Specification Issue Date: JuLy 27, 2011