



**Safetyflex® Jacket**

**Stock Number - J41108**



**Compliance Standards:** Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

**Garment Detail:**

The jacket has tapered raglan sleeve construction with a 90 degree sleeve-to-body angle, a storm fly front with hidden snap closure, an inner storm flap, and an attached hood with drawcord.

**Garment Type:** High performance rainwear, provides superior protection against acids, caustics, and chemicals.

**Sizes:** S, M, L, XL, 2X, 3X, 4X

**Color:** Green

**Material:** Green material is 13 oz./yd<sup>2</sup> Specialty PVC on 150D Polyester.

**Seam Construction:** All seams are RF/heat sealed and 100% waterproof.

**Closure Type:** Hidden snap closure with 4 snaps and storm fly.

**Pockets:**

**Labels/Tags:**

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

**Packaging:** Printed polyethylene bag.

**Other:** Mildew Resistant.

Dimensions	S	M	L	XL	2X	3X	4X
Chest	46"	50"	54"	58"	62"	66"	70"
Length	29"	30"	31"	31"	32"	32"	32"
Sleeve Length	34"	34"	34.5"	35"	35.5"	36"	36"

**Case Pack:** 12 each

**Case Dimensions/Weight**

S = 15"(L) X 13"(W) X 11"(H) / 18 lbs.      2X = 15"(L) X 13"(W) X 11"(H) / 23 lbs.

M = 15"(L) X 13"(W) X 11"(H) / 19 lbs.      3X = 15"(L) X 13"(W) X 11"(H) / 25 lbs.

L = 15"(L) X 13"(W) X 11"(H) / 20 lbs.      4X = 15"(L) X 13"(W) X 11"(H) / 25 lbs.

XL = 15"(L) X 13"(W) X 11"(H) / 22 lbs.

Safetyflex® is a registered trademark of Tingley Rubber Corp.