#### 2011





# Bringing you the ultimate in commercial value!

### All R-410A refrigerant!

### **Split Condensing Units**

#### 3 - 5 Tons


#### HC4A3

- 13 SEER
- · Scroll compressor
- 208/230 or 460 volts



#### 3 - 5 Tons

- **H4A3** 13 SFFR
- Scroll compressor
- · 2-speed fan motor
- · 20°F. low ambient control
- Comfort Alert® diagnostics\*
- comport Alert alagnostic





#### 2.5 - 5 Tons

- N4A3
   13 SEER
- Scroll compressor
- 208/230, 460 or 575 volts

#### 6 Tons

#### CAS072

- · ASHRAE 90.1 efficiency
- 11.2 FFR
- Scroll compressor
- · Comfort Alert® diagnostics\*
- Low ambient control option (-20°F.)
- 208/230, 460 or 575 volts

#### 7.5 - 12.5 Tons

- CASO91, CAS121, CAS151
   ASHRAE 90.1 efficiency
- Up to 11.2 EER
- Scroll compressor
- · Single refrigerant circuit
- Comfort Alert® diagnostics\*
- Low ambient control option (-20°F.)
- 208/230, 460 or 575 volts

#### 10 - 12.5 Tons CAS120, CAS150

- ASHRAE 90.1 efficiency
- 11.2 EER
- Dual scroll compressors
- Comfort Alert® diagnostics\*
- Low ambient control option (-20°F.)
- 208/230, 460 or 575 volts

#### 15 & 20 Tons

### CAS180, CAS181, CAS240, CAS241

- · ASHRAE 90.1 efficiency
- 11.0 EER
- Scroll compressor
- Single or Dual refrigerant circuit
- Comfort Alert® diagnostics\*
- Low ambient control option (-20°F.)
- 208/230, 460 or 575 volts

### Split Heat Pumps

#### 3 - 5 Tons

#### HC4H3

- 13 SEER7.7 HSPF
- 7.7 HSPFScroll
- compressor

#### • 208/230 or 460 volts

#### 3 - 5 Tons

### H4H3 • 13 SEER

- 13 SEER
- Up to 8.5 HSPFScroll compressor
- · 2-speed fan motor
- Comfort Alert® diagnostics\*
- 208/230 or 460 volts

#### 2.5 - 5 Tons

#### N4H3

- 13 SEER
- Scroll compressor
- 208/230 or 460 volts

#### Heil® commercial products are covered by the following parts-only limited warranties:

- Compressor 5 Yrs.
- Parts 1 Yr

### Split Heat Pumps cont.

#### 6 - 20 Tons

### CHS072, CHS091, CHS121, CHS180, CHS240

- · ASHRAE 90.1 efficiency
- Up to 11.0 EER
- Scroll compressor
- Single refrigerant circuit on CHS072, CHS091, CHS121
- Dual refrigerant circuit on CHS180, CHS240 models
- Comfort Alert® diagnostics\*
- Low ambient control option (-20°F.)
- 208/230, 460 or 575 volts

## Commercial Air Handlers

#### 6 - 25 Tons

### FASO72, FASO91, FAS120, FAS150, FAS180, FAS240,

- FAS300
   AC fan coil
- TXV standard
- 4-row coil
- Optional High-static fan motor
- Painted or unpainted cabinet
- Multi-position
- 5 70 kW electric heat
- 208/230/460 or 575 volts

#### 6 - 20 Tons

### FHS072, FHS091, FHS120, FHS180, FHS240

- HP fan coil
- TXV standard
- 4-row coil
- Optional High-static fan motor
- Painted or unpainted cabinet
- Multi-position
- 5 70 kW electric heat
- 208/230/460 or 575 volts

15 - 20 ton unit shown



<sup>\*</sup> Comfort Alert° is a registered trademark of Emerson Climate Technologies, Inc