



ECN	REV	ZONE	DESCRIPTION	CHK	D	DATE
XXXXXXXX	A	XXXXX		-	GL	

MODEL	DIMENSIONS		
	W"	D"	H"
GSZ160181L*	29	29	36 ³ / ₈
GSZ160241L*	35 ¹ / ₂	35 ¹ / ₂	34 ⁵ / ₈
GSZ160301L*	35 ¹ / ₂	35 ¹ / ₂	34 ⁵ / ₈
GSZ160361L*	35 ¹ / ₂	35 ¹ / ₂	40
GSZ160421L*	29	29	36 ³ / ₈
GSZ160481L*	35 ¹ / ₂	35 ¹ / ₂	34 ⁵ / ₈
GSZ160601L*	35 ¹ / ₂	35 ¹ / ₂	40

SPECIAL CHARACTERISTICS:

6SIGMA

CRITICAL CHARACTERISTIC

SIGNIFICANT CHARACTERISTIC

COMPONENTS AND MATERIALS SPECIFIED HEREIN WILL ALSO CONFORM TO THE APPLICABLE SECTION OF GOODMAN MSP 824.01 WORKMANSHIP STANDARD FOR FIT, FEEL AND FINISH.

CONFIDENTIAL PROPERTY OF THE GOODMAN MANUFACTURING COMPANY, L.P. NOT TO BE DISCLOSED TO OTHERS, COPIED, OR USED FOR ANY PURPOSE EXCEPT AS AUTHORIZED IN WRITING. MUST BE RETURNED UPON DEMAND, ON COMPLETION OF ORDER, OR OTHER PURPOSE FOR WHICH IT WAS LENT.

Goodman Manufacturing Company, L.P.

GSZ16 Heat Pump

DRAWING TO BE INTERPRETED IN ACCORDANCE WITH ASME Y14.100 DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED

TOLERANCES:
ANGLES ± 1.5°
X: ± .1
ZK: ± .03

DWN BY:

ENG:

DO NOT SCALE DRAWING
SHT 1 OF 1

XXX: ± .015
HOLE Ø: ± .005
TUBE CUT LG: ± .063



REV
A