

135-160 Alto™

Elongated Front, Vitreous China, Two-Piece Toilet

Features

- Contemporary design
- Superior boxed rim, siphon jet SmartFlush[™] technology
- 1.6 gpf / 6.0 lpf low water consumption
- Two-inch glazed trapway
- 12" Rough-in

SB1200

- Large 8-1/16" x 9-5/16" water surface
- Available in White, Standard Colors: Biscuit, Classic Bone and Designer Colors: Black, Classic Silver
- Model 40 chrome plated plastic trip lever (Consult Price Book for additional finishes)
- Upgrade with a color-match SmartClose[™] or Primo[™] toilet seat
- Meets or exceeds ANSI/ASME A112.192 and A112.19.6
- Meets or exceeds Canadian Standards Association B45.0
- Outstanding protection The Mansfield[®] limited lifetime warranty

Elongated Front

Model 135-160 Shown with SB1200 Primo™ toilet seat

Model No.	Description	Approx. Wt.
135-160	Elongated front, (1.6 gpf/6.0 lpf) two-piece toilet. 12" rough-in. Includes tank trim and chrome plated plastic trip lever. Less toilet seat and supply. Specify colo	78 lbs. (35.1 kg) pr.
135	Elongated front, toilet bowl only. 12" rough-in. Less toilet seat. Specify color.	47 lbs. (21.1 kg)
160	Tank and cover only, with left hand, chrome plated, plastic trip lever. Less supply. Specify color.	31 lbs. (13.9 kg)
125	Same as model 160, except with 14" rough-in.	33 lbs. (15 kg)
160RH	Same as model 160, except with right hand trip lever.	31 lbs. (13.9 kg)
161	Same as model 160, except with Fluidmaster™ 400A ballcock.	33 lbs. (15 kg)
165	Same as model 160, except with cover lock.	31 lbs. (13.9 kg)
170	Same as model 160, except with tank liner.	31 lbs. (13.9 kg)
171	Same as model 160, except with tank liner and Fluidmaster™ ballcock.	31 lbs. (13.9 kg)
175	Same as model 160, except with cover lock and tank liner.	31 lbs. (13.9 kg)
180	Same as model 160, except with color-match trip lever.	31 lbs. (13.9 kg)
181	Same as model 160, except with Fluidmaster™ 400A ballcock and color-match trip lever	33 lbs. (15 kg)
190	Same as model 160, except with color-match trip lever and tank liner.	31 lbs. (13.9 kg)
SB400	Elongated, SmartClose™ toilet seat.	5.5 lbs. (2 kg)

Elongated, Primo[™] toilet seat.





5.5 lbs. (2 kg)

135-160 Alto™ Elongated Front, Vitreous China,

Two-Piece Toilet

Features & Upgrades

Three-Point Cushioned Tank-to-Bowl Connection

This assures perfect tank alignment in every direction. It permits fast, accurate, leakproof tank-to-bowl connections. Protects against tank breakage...can't be rocked loose... saves installation time. Furnished with brass nuts and bolts.

211 Flush Valve

The 211 flush valve provides 1.6 gpf – 6.0 lpf water conservation efficiency with non-corrosive, long-life dependability. It seals tight every time. Won't rust or corrode.





88 Anti-Siphon Ballcock

The 88 anti-siphon ballcock affords efficient toilet tank operation at high or low pressures. Adjustment screw allows water level adjustment without bending the float rod. Completely non-eletroytic and non-corrosive.

Add a Toilet Seat

With a simple touch, Mansfield's SmartClose™ toilet seat gently and quietly. Or upgrade your toilet with a popular Primo™ toilet seat. Made of durable, high impact, heavy-duty plastic. For all applications -Get More, Get Mansfield®.





Technical Information

Specifications

Specifications			
Material	Vitreous China	Finished Wall	0.4/0
Water Pressure Range	20 to 80 P.S.I		9-1/2" (241 mm)
Flush System	SmartFlush™ Flushing Technology	14-1/2" (368 mm)	6" (152 mm
Water Usage	1.6 gpf / 6.0 lpf (140 mm Typ.		
Water Surface Area	8-1/16" x 9-5/16"	(254 mm) 19 (48	I-1/4" Toilet 9 mm) Ecotorint
Trap Diameter	2"		^{9 mm)} Footprint
Trap Seal	2-5/8" 1" —	→ 13-1/4" → (337 mm)	
Rough-in	12" (14" Option) (25 mm)	(476 mm)	
Shipping Dimensions	Model 135 27-1/4" x 14-7/8" x 15-1/2" (692 mm x 378 mm x 394 mm)	29-3/4"	19-3/4" (502 mm)
	Model 160 19-3/4" x 10" x 14-3/4" (501 mm x 254 mm x 375 mm)	29" (737 mm)	
Shipping Weight	Model 135 - 46.9 lbs (21kg)		
	Model 160 - 34.1 lbs (15 kg)		
Warranty	Vitreous China - Limited Lifetime Tank Trim - Limited One Year	14-3/4" (375 mm) 8" Typ	Finished Floor
These dimensions are no without prior notice.	ominal and are subject to change		
	d specifications meet or exceed, ndards and CSA B45 standard, I codes.	(305 mm)	6" Typ. (152 mm) 3/8" (10 mm) N.P.S Supply

> NOTE: Install this product according to the installation guide. Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2

See our complete line of acrylic and vitreous china bathroom fixtures, plastic tank trim and plumbing products.

mansfield.

Mansfield Plumbing Products LLC • Customer Service Toll Free 877-850-3060 • Fax 419-938-6234 Website: www.mansfieldplumbing.com • Email: custserv@mansfieldplumbing.com Form No. M135160 Printed in U.S.A. 7/09

© 2009 Mansfield Plumbing Products LLC