PP912SM

GE Profile™ 30" Built-In CleanDesign Electric Cooktop

Dimensions and Installation Information (in inches)

KW Rating	
240V	7.6
208V	5.7
Breaker Size	
240V	40 Amps†
208V	30 Amps [†]

†Note: Check local codes for required breaker size Important: Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.


Note: 30" Ribbon cooktops are approved for use over select GE 27" and GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current -dimensional data. If installed with a GE Profile™ Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. Consult cabinet and countertop manufacturer's specs for flush mount installation prior to install. Before installing, consult installation instructions packed with product for current dimensional data.

Filler Trim Kit: When replacing an old GE 30" cooktop (with larger opening) use the following one-piece trim kit to fill in the over-size hole. Available at additional cost. JXTR32W (True White) JXTR32B (Black glass), JXTR32C (True Bisque)

29-7/8 21-1/2 3.1/4*
Cooktop 3.1/4*

28-1/2 Pequired

- *Depth of unit at conduit connection location (rear) is 6-1/2" on models PP980/950 and 4-5/8" on models PHP900/PP975/972/962/945/942/932/912, JP655/356/346.
- **Raised bull nose countertops may require up to 3/8" additional clearance to prevent interference with curved front.



For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at ge.com or call GE Answer Center® service, 800,626,2000





PP912SM

GE Profile™ 30" Built-In CleanDesign Electric Cooktop

Features and Benefits

- Ceramic Glass Cooktop A smooth cooktop surface makes cleaning quick and easy
- Ribbon Heating Elements Provide powerful heat beneath a smooth glass surface to ensure even heat and fast warm-up times
- Dual Size Ribbon Element Offers a convenient choice of using a 9" or 12" heating element, depending on the size of the pan
- PowerBoil™ Element Provides up to 3,000 watts of power to speed the boiling process
- Stainless Steel Frame Brings an added touch of style to any decor and perfectly complements all other stainless steel appliances in the kitchen
- Heavy-Duty Die-Cast Knobs Add durability and brushed chrome for enhanced style and performance
- Dishwasher-Safe Knobs Feature a robust construction for safe and easy cleaning
- Melt Setting Optimized for melting chocolate, this setting delivers the low gentle heat needed
- Control Lock Capability Provides the ability to lock controls, helping protect from unintentional activation
- Model PP912SMSS Stainless steel

