

# PIPE JOINT LUBRICANT

## Product Features

- All purpose pipe lube is used to assemble pipes made of cast iron, concrete, plastic and clay pipe.
- Suitable for all types of pipes, including potable water systems
- Can be applied in temperatures from 0° F to 150° F
- Contains no petroleum, phosphate or silicone
- Will not support bacteria growth
- Biodegradable
- Non-toxic

## Certification and Approvals

- NSF/ANSI Standard 61 compliant
- Complies with Calif. AB-1953 and Vermont Act 193
- FGG/BM/CZ™ System Compatible\*

Pipe Diameter (inches)	Estimated Pounds of Lube per 100 Joints
4	3
6	4
8	4
10	5
12	6
15	10
18	12
21	14
24	16
27	18
30	21
36	26
42	31
48	37
54	42
60	50
66	57
72	64
78	70
84	78

**PSLUBQT**  
**PSLUBGAL**  
**PSLUB5GAL**



## Directions for Use

- Clean all joint surfaces. Make certain that the gasket is properly positioned.
- Apply an even coating of lubricant to the inside of the bell and outside of spigot and gasket.
- Assemble the joint according to the pipe manufacturer's directions.

## Product Specifications

Model Number	Description	Carton Weight
PSLUBQT	Pipe Joint Lubricant	1 quart or 2 lbs
PSLUBGAL	Pipe Joint Lubricant	1 gallon or 8 lbs
PSLUB5GAL	Pipe Joint Lubricant	5 gallons or 40 lbs

\*FGG/BM/CZ™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FGG/BM/CZ™ FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings. FGG/BM/CZ™ FlowGuard Gold®, BlazeMaster®, and Corzan® are licensed trademarks of The Lubrizol Corporation.

