

Fast Trak™ Edge Strip

Submittal Information Revision A: April 14, 2011

Revision A: April 14, 2011
Project Information

Job Name:

Job Name.	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

Technical Data

Material:

Expanded polyethylene foam, polyethylene foil



Product Information and Application Use

Fast $Trak^{\text{TM}}$ Edge Strips install between the load distribution layer and the vertical building parts, covering the edge joint. The Edge Strips prevent overpour from seeping under the Fast Trak panels and protect the surrounding structure from moisture damage and expansion forces.

✓	Description	Part Number	Length	Height	Thickness	Weight
	Fast Trak Edge Strip, 65-ft. roll	A5091000	65'	3.5"	0.315"	1.0 lb.

Installation

The existing edge joint must always include Edge Strips to the height of the leveling layer and the new floor covering to be installed. When installing Edge Strips, ensure polyethylene foil is laying down on the subsurface. It is important not to remove the protruding sections of the Edge Strips until the floor covering is installed. For further information, see the Fast Trak Installation Guide.

www.uponor-usa.com

Standards

N/A

Codes

N/A

Listings

N/A

Related Applications	Contact Information				
Radiant Heating and Cooling Systems	Uponor, Inc. 5925 148 th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739				

Uponor Ltd. 2000 Argentia Road, Plaza 1, Suite 200 Mississauga, ON L5N 1W1 CANADA Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca