Brass Craft_®



HWATER HERES HERE



KT[™] Series 1/4 Turn Ball Stops







Just like you, the BrassCraft® KT™ Series

¼ Turn Ball Stops outperform — stopping
at nothing to get the job done right.

Designed, Machined and Assembled
in the U.S.A., these stops provide
uncompromising quality, dependability
and innovation. With premium features, a
sleek appearance and ease-of-use, the KT
Series ¼ Turn Ball Stop is nothing short of
brilliant. That is why plumbers have trusted
BrassCraft products for more than 65 years.

Every KT Series ¼ Turn Ball Stop offers:

High Performance Seats Uniquely designed PTFE seats provide corrosion resistance and a watertight seal while assuring ease of use, even after long periods of time.

Precision — **Machined Brass Ball** Specially engineered brass ball mated with PTFE seats resists corrosion, provides long life and ensures ease of operation.

Chrome-Plated Brass Body Machined one-piece brass body for strength and durability with chrome finish for corrosion resistance and fine appearance.

Double 0-Rings Ensures safe, reliable performance.

Plated Stem Provides corrosion resistance and prevents o-ring damage after long periods of non-use.

Chrome Plated, Metal Handle Designed for durability, corrosion resistance, and a sleek appearance.

100% Leak Tested Each stop is leak tested to ensure reliability.

Compliant KT Stops Meets "no-lead" requirements.

The KT Series ¼ Turn Ball Stop by BrassCraft Manufacturing – with uncompromising quality and superior performance, it stops short of nothing.

Committed to Quality, Driven by Innovation





Brass Craft





BrassCraft Manufacturing Co. 39600 Orchard Hill Place Novi, Michigan 48375-5331 TOLL FREE (877) 272-7755 FAX: (248) 305-6011

www.brasscraft.com

35 Currah Road St. Thomas, Ontario N5P 3R2 (519) 633-0340 FAX: (519) 633-0777

©2013 BrassCraft Mfg. 0693 1/13

For Residential and Commercial Applications					
Job Name	Engineer / Architect				
Job Location	Wholesaler				
Submittal Date	Contractor				

KTR04X / KTR14X 1/4 Turn Straight Ball Stop - Sweat x Compression

Use: For use only in potable water distribution systems, hot and cold, in accessible locations only.

Design Features:


- Machined brass ball is specially engineered and mated with PTFE seats to provide smooth operation without freeze ups even after long periods of non-use
- Two high-performance o-rings withstand high temperatures and corrosion from harsh water environments
- Machined, one-piece brass body provides strength, durability, and long-lasting performance
- Brass stem is assembled from the inside out with two o-rings to ensure safe, reliable performance
- Plated stem provides corrosion resistance and prevents o-ring damage after long periods of non-use
- Exclusive, chrome-plated metal handle is designed for durability, corrosion resistance, and a sleek appearance
- Easy-to-remove handle with screw attachment protects accidental stop operation during rough-ins
- 100% leak tested
- **Ø** No Lead

Operating Specifications:

Temperature: 40°-180° F

Pressure: 125 PSI maximum

MATERIAL SPECIFICATIONS					
Body	Brass or brass, chrome plated				
Stem	Brass, plated				
Seat	PTFE				
Ball	Brass, plated				
Stem o-ring	Rubber				
Handle	Zinc, die cast plated				
Handle Screw	Steel, zinc plated				
Compression Sleeve	Brass				
Compression Nut	Brass or brass, chrome plated				






KTR04X / KTR14X 1/4 Turn Straight Ball Stop - Sweat x Compression

Part Listing:						
	KTR04X R	1/2" nom sweat x 1/4" OD compression, rough brass				
	KTR04X RM	1/2" nom sweat x 1/4" OD compression, rough brass, contractor 5 pack				
	KTR14X C	1/2" nom sweat x 3/8" OD compression, chrome plated				
	KTR14X C1	1/2" nom sweat x 3/8" OD compression, chrome plated, window tray				
	KTR14X CM	1/2" nom sweat x 3/8" OD compression, chrome plated, contractor 5 pack				
	KTR14L1X CB	1/2" nom sweat x 3/8" OD compression, less nut, chrome plated, bulk				
	KTR14X R	1/2" nom sweat x 3/8" OD compression, rough brass				
	KTR14X RM	1/2" nom sweat x 3/8" OD compression, rough brass, contractor 5 pack				

PART DIMENSIONS (Inches)							
Model	DIM. A	DIM. B	DIM. C	DIM. D			
KTR04X	1.14	2.05	1.55	.81			
KTR14X	1.14	2.08	1.55	.81			



Listings & Certifications:

- IAPMO listed to ASME A112.18.1 / CSA B125.1 (Including NSF 61 and NSF 372)(File 0645)
- CSA listed to ASME A112.18.1 / CSA B125.1 (Including NSF 61 and NSF 372)(File 204593)
- No-lead product CSA listed to NSF 372 (Class 6853-01)











