

# Specifications

## HEADRAIL

Extruded PVC  
1.135" width x  
.935" height x .070"  
thick for widths up  
to 68". At 69" and  
wider the headrail  
measures 1.500"  
width x 1.500"  
height x .070" thick.

## BOTTOMRAIL

Extruded hollow  
PVC 1.035" width x  
.450" height x .055"  
thick.

## WAND

Extruded PVC Hex  
shape, .315" across  
flats. Color coordi-  
nated.

## SLAT

Extruded PVC  
.0157" thick x .970"  
width with crown of  
.160". 75% opacity.  
Flammability test-  
ing passed NFPA  
701 small scale test.

## TAPE ROLLER

### SUPPORT

Injection molded  
plastic with metal  
roller minimizing  
cord fray.

## TAPE ROLLER

Injection molded  
plastic with ladder  
locking legs.

## TIlt ROD

Plated steel,  
"O" shape  
.150" x .125"

## CORDLOCK

Injection molded  
plastic. Smooth  
brass fixed roller.  
Knurled floating  
brass roller.

## HOLD DOWN

### BRACKETS

Injection molded  
plastic.

## TILTER

Injection molded  
plastic housing  
with steel wand  
hook. Gear ratio of  
9 to 1. Metal rivet  
for added strength.

## BOTTOMRAIL

### ANCHORS

Injection molded  
plastic face .500"  
diameter, stem  
.375" diameter.

## BOTTOMRAIL

### ENDCAPS

Injection molded  
plastic.

## SLAT CLIP

Injection Molded  
Clear Plastic.

## CORD

Woven polyester  
.070" diameter.

## LADDER

Woven polyester  
.840" spacing x  
1.000" width.

## CENTER SUPPORT

Plated steel .040"  
thick.

## TASSEL

Injection molded  
plastic - bell  
shaped.

## MOUNTING

### BRACKET

Color coordinated  
injection molded  
plastic. Suitable for  
inside or outside  
mount.



Headrail



Heavy duty tilter  
with metal rivet



Cordlock with  
brass roller



Bottomrail of  
extruded hollow  
PVC



Child-safe tassel  
& Safety warning tag

# Packaging

Up to 47" wide: 6 per carton  
48" wide and larger: 4 per carton