



Defoamer

A fast-acting foam preventer for recovery tanks.

Productive

- Helps reduce foaming to significantly reduce empty cycles during carpet and hard floor cleaning

Versatile

- Works in hoses, tools and recovery tanks
- Works with both hot and cold water

Environmentally-Friendly

- pH neutral and phosphorus-free
-



Defoamer



Use Directions

- Shake well before use.
- Add 1 oz. of Defoamer to every 10 gallons capacity of recovery tank (30 mL per 37.8 L).
- For tools and hoses, pour approximately 1/2 oz. (15 mL) into tool or hose assembly.
- Additional Defoamer may be used depending on amount of residue in carpet.

Caution: Do not allow product to get directly on to hard surface floors as it may leave the floor slippery. To remove product scrub the floor with detergent and dry thoroughly.

Product Specifications

Description	
Color/Form	Milky cream, liquid
Flash Point	>200° F (>93.3° C)
pH	8.25 (Concentrate)
Scent	Bland
Shelf Life	2 years
Solubility	Complete
Specific Gravity	1.003

Available Items

Product Code	Description/Package Size	Dilution
5002620	6 x 32 oz. / 946 mL Squeeze Bottles	Ready-to-Use

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available on-line at www.sealedair.com or by calling 888 352 2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up to date shipping information.