

# Bancroft® Rite-Temp® Bath and Shower Valve Trim K-TLS10582-4P

# Features

- Includes face plate with handle, bath spout, shower arm with flange.
- Single handle controls both on/off activation and temperature setting.
- Supplied with white ceramic lever handle.
- Includes diverter bath spout with 1/2" copper slip fit connection.
- For use with any KOHLER showerhead (not supplied).
- Complements the Bancroft<sup>®</sup> faucet and accessory collections.

# Material

- Premium material construction with ceramic handle ensures reliability and durability.
- KOHLER finishes resist corrosion and tarnishing, exceeding industry durability standards.

## Installation

• Trim set requires valve to complete installation.

# **Required Accessories**

K-304/K-P304 Series Rite-Temp® Valves

or

K-8304/K-P8304 Series Rite-Temp $\ensuremath{\mathbb{R}}$  Valve & Cartridge Kits or

K-8300/K-P8300 Series Rite-Temp® Valve Body Rough-ins K-8305/K-P8305 Series Rite-Temp® Cartridges

or

K-2971-KS 3/4" Pressure-balancing Valve

## **Optional Accessories**

K-10350 Deep Rough-In Kit For K-8305 Cartridges K-10351 Test Cap For K-8300 Series Valve Bodies







# Codes/Standards

ASME A112.18.1/CSA B125.1 California Energy Commission (CEC)

# KOHLER<sup>®</sup> Faucet Lifetime Limited Warranty

See website for detailed warranty information.

# **Available Color/Finishes**

Color tiles intended for reference only.

## Color Code Description

CP	Polished Chrome
SN	Vibrant® Polished Nickel
BN	Vibrant® Brushed Nickel


BV Vibrant® Brushed Bronze





# **Bancroft**®

Rite-Temp<sup>®</sup> Bath and Shower Valve Trim K-TLS10582-4P



# **Technical Information**

All product dimensions are nominal.

## Notes

Install the product according to the installation guide.

NOTICE: Risk of product damage. Long screws for installing trim can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit (88526) is needed.

Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between the valve and the wall-mount spout. Elbow must be a 90 degree drop ell that is secured to rigid framing.

